

# HOME CHOICE

## CARPETS

### Product Data Sheet

### CAR-OXF-CAM



Scan the QR code for fast access to this floor online

## Home Choice Home Choice Oxford Campus Grey Twist Pile Carpet 13mm

Our UK-made Home Choice Oxford Twist Pile carpet range is as comfortable as it is durable. There's no need to worry with this carpet as the twist pile and stain-resistant construction means it can handle busy areas in even busier homes. Enjoy the upmost comfort with each step as you sink your toes into the plush 10mm thick twist pile. The combi backing made of fleece and woven polypropylene results in a strong and stable carpet that will add even more softness and insulation to any room it is fitting in.

A classic style that works in any room of choice, our Oxford Campus Grey carpet is perfect if you're looking to add a simple yet super stylish look. Thanks to the 2-ply build of the Oxford range, this carpet interweaves two similar tones to provide this beautiful grey textured finish. Renowned for their hard-wearing nature, twist pile carpets are perfectly suited to the busiest of areas in your home, from your hallway entrance to your landing, no matter how many footsteps your space encounters, this carpet is ready for it all.

### Product Details

<b>Code:</b>	CAR-OXF-CAM
<b>Brand:</b>	Home Choice
<b>Construction:</b>	Twist
<b>Material:</b>	100% Polypropylene
<b>Pile Height (mm):</b>	10mm
<b>Thickness:</b>	13mm
<b>Ply:</b>	2-Ply
<b>Backing:</b>	Combi-Back
<b>Suitability:</b>	Bedroom, Dining Room, Hallway, Lounge, Stairs heavy use
<b>Moth Protection:</b>	Yes
<b>Stain Protection:</b>	Yes
<b>Over floor heating:</b>	Yes, Water Systems up to 27°C and check with the manufacturer before installation

### Warranty

<b>Residential:</b>	10 year
---------------------	---------

### Technical

<b>Gauge:</b>	1/10
<b>Tog:</b>	1.91
<b>Technical Class:</b>	Class 32 General Commercial
<b>Fire Classification:</b>	Efl sl
<b>Hot metal nut test:</b>	High Radius of Char
<b>Pile Weight:</b>	
<b>Tuft per m2:</b>	144357
<b>Underlay Recommendation:</b>	Minimum 8mm underlay recommended

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
 Tel: 02476 012840 | Fax: 02476 397828  
 info@ukflooringdirect.co.uk  
 ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.