

GALLERIA PROFESSIONAL

Product Data Sheet ENG-GA-15-150



Scan the QR code for fast access to this floor online

Galleria Professional Engineered Select Oak Chevron Flooring 15mm x 110mm Ecru Brushed & Lacquered

If you're looking to install a stunning real wood floor, then look no further than our Galleria Professional Engineered Wood flooring. Offering exceptional stability, the floor features a high-quality multi-layer construction of several layers of plywood topped with a 3mm hardwood wear layer for a dense feel underfoot and optimum grain definition. With a traditional tongue-and-groove fixing, this load-bearing floor requires professional installation for best results. Keep cosy all year round as this flooring is perfectly suitable with underfloor electric and water heating systems up to 27°C.

Our Galleria Professional Engineered Select Oak Chevron Flooring in Ecru symbolises freshness and modernity with a striking chevron effect pattern that creates an eye-catching look. The clean veneer of the select grain, which has minimal sapwood and only a few small knots, creates an unbeatable look that's lifted by the brushed finish. Plus, finished with a high-quality UV lacquer to give an attractive subtle sheen, whilst offering this beautiful parquet floor a truly natural look that will suit a wide range of interior styles. Simply vacuuming and using a damp mop occasionally is all that is needed to maintain this floor.

Product Details

Brand: Galleria Professional Construction: Engineered Multi-Ply Surface: Brushed Profile: Tongue & Groove Edge profile: Bevelled on 4 sides Thickness: 15mm Width: 110mm Length: 500mm Coverage per pack: 0.88m²	Code:	ENG-GA-15-150
Surface: Brushed Profile: Tongue & Groove Edge profile: Bevelled on 4 sides Thickness: 15mm Width: 110mm Length: 500mm	Brand:	Galleria Professional
Profile: Tongue & Groove Edge profile: Bevelled on 4 sides Thickness: 15mm Width: 110mm Length: 500mm	Construction:	Engineered Multi-Ply
Edge profile: Bevelled on 4 sides Thickness: 15mm Width: 110mm Length: 500mm	Surface:	Brushed
Thickness: 15mm Width: 110mm Length: 500mm	Profile:	Tongue & Groove
Width: 110mm Length: 500mm	Edge profile:	Bevelled on 4 sides
Length: 500mm	Thickness:	15mm
	Width:	110mm
Coverage per pack: 0.88m ²	Length:	500mm
	Coverage per pack:	0.88m²

Installation

Fully bonded:	Yes
Floated on underlay:	No
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

Technical

Max side of sound knots:	30mm in diameter
Max size of broken knots:	30mm diameter
Sapwood:	Acceptable up to 30% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 2mm wide & 100mm long
Inner bark:	Allowed
Origin of timber:	Europe
Layers of lacquer/oil	6

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ Tel: 02476 012840 | Fax: 02476 397828 info@ukflooringdirect.co.uk ukflooringdirect.co.uk

Warranty

Residential:	N/A
Commercial:	N/A

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.