



# GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



## Product Data Sheet

**ENG-GAL-001**

Scan the QR code for fast access to this floor online

## Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Lacquered

A premium engineered wood floor that is as hardwearing as it is beautiful, Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Lacquered is an investment for life.

Blessed with warm oak tones and a relaxed, natural appearance, this truly timeless floor will add a welcoming feel to any room in the home. Made using finest European oak in a rustic grade – characterised by lively grain markings, knots of all sizes, sapwood and small mineral streaks – it has been sanded smooth and finished treated with a high-quality lacquer to provide excellent protection and ease of maintenance; regular vacuuming and occasional damp-mopping will ensure it stays looking fabulous.

The wide, long-length planks (190mm x 1900mm) are ideally suited to spacious interiors, particularly longer rooms where they will help make the floor look in proportion and add to a feeling of elegance. Offering exceptional stability, this load-bearing tongue-and-groove floor is 20mm thick and features a multi-layer construction of several layers of plywood topped with a 6mm hardwood wear layer for a dense feel underfoot and optimum grain definition. For best results, professional installation is recommended.

### Product Details

<b>Code:</b>	ENG-GAL-001
<b>Brand:</b>	Galleria Professional
<b>Construction:</b>	Engineered Multi-Ply
<b>Species:</b>	Oak
<b>Grade:</b>	Rustic
<b>Design:</b>	Plank
<b>Surface:</b>	Smooth
<b>Finish:</b>	UV Lacquer
<b>Profile:</b>	Tongue & Groove
<b>Edge profile:</b>	Bevelled on 4 sides
<b>Top layer:</b>	6mm
<b>Core:</b>	Softwood
<b>Thickness:</b>	20mm
<b>Width:</b>	190mm
<b>Length:</b>	1900mm
<b>Coverage per pack:</b>	1.81m <sup>2</sup>

### Warranty

<b>Residential:</b>	N/A
<b>Commercial:</b>	N/A

NB: Please ask for full warranty terms and conditions

### Installation

<b>Fully-bonded:</b>	Yes
<b>Nailed:</b>	Yes
<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes, Water Systems up to 27 °C

### Technical

<b>Max side of sound knots:</b>	50mm diameter
<b>Max size of broken knots:</b>	40mm diameter
<b>Sapwood:</b>	Acceptable up to 30% of the board
<b>Filler &amp; colour variation:</b>	Allowed
<b>Small cracks:</b>	Acceptable up to 5mm wide & 300mm long
<b>Inner bark:</b>	Allowed
<b>Origin of timber:</b>	Europe
<b>Responsible certification:</b>	N/A
<b>Janka hardness rating:</b>	1360

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.