



# HOME CHOICE

floors made for living

UK **FLOORING** DIRECT



## Product Data Sheet

**ENG-HC-14-028**

Scan the QR code for fast access to this floor online

## Home Choice Engineered European Select Oak Flooring 14mm x 130mm Pudding Piccolo Lacquered

If you're seeking a wood floor that's family friendly but also has a cool, contemporary vibe, Home Choice Engineered European Select Oak Flooring 14mm x 130mm Pudding Piccolo Lacquered is for you.

Boasting attractive pale oak tones that complement a wide range of interior schemes, this stylish floor is made using high-quality European oak in a select grade, with minimal sapwood, few knots and less pronounced colour variation for a clean, understated look. The boards have been sanded smooth to let the expressive oak grain play its part and are finished with a premium UV lacquer that protects against stains and wear and tear.

The planks come in a versatile standard size (130mm x 1100mm) that is particularly well suited to small and medium-length rooms, where they will create a relaxed, classic look and help enhance the feeling of space.

Featuring a three-layer construction for durability and a 2.5mm real wood wear layer for long-lasting good looks, Home Choice Engineered European Select Oak Pudding Piccolo Lacquered offers fast and easy DIY fitting thanks to its 5GC click-together system. A modern floor that's both stunning and easy to care for; simply vacuum and damp mop to keep it looking its best.

### Product Details

Code:	ENG-HC-14-028
Brand:	Home Choice
Construction:	Engineered 3-Ply
Species:	Oak
Grade:	Select
Design:	Plank
Surface:	Smooth
Finish:	UV Lacquer
Profile:	5GC Click System
Edge profile:	Bevelled on 4 sides
Top layer:	2.5mm
Core:	Softwood
Thickness:	14mm
Width:	130mm
Length:	1100mm
Coverage per pack:	1.00m <sup>2</sup>

### Warranty

Residential:	20 Years
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

### Installation

Fully-bonded:	Yes
Nailed:	No
Floated on underlay:	Yes
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

### Technical

Max side of sound knots:	35mm diameter
Max size of broken knots:	25mm diameter
Sapwood:	Acceptable up to 10% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 5mm wide & 200mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.