



AQUALOCK

WATER RESISTANT FLOORS

Product Data Sheet

LAM-AL-10-005

UK **FLOORING** DIRECT



Scan the QR code for fast access to this floor online

Aqualock Aqualock 10mm Laminate Flooring Shore Oak

Nothing can come close to the timeless appeal of a traditional wood-effect floor like Aqualock 10mm Laminate Flooring Shore Oak. With its gorgeous natural oak tones that carry a premium look and feel thanks to embossed surface markings, it creates the perfect relaxed vibe that will make any room feel more welcoming in an instant. The welcome can be made even warmer thanks to this floor's compatibility with water-based underfloor heating systems. This is just one of the many benefits reaped from modern laminate construction, as this floor also boasts 72-hour water-resistance for added protection against moisture and spills, as well as UV resistance to help prevent fading.

Thanks to its bevelled edge boards that measure in at 1285mm x 158mm, Aqualock 10mm Laminate Flooring Shore Oak is ideally proportioned to fit into most rooms. It is also fast and easy to install, even for novice fitters, thanks to its DIY-friendly click system. You'll have peace of mind with this floor too with its 25-year residential warranty, 5-year commercial warranty and its AC5 Commercial rating. Easy to maintain and simple to care for, Aqualock Laminate Flooring just needs vacuuming regularly and cleaning occasionally with a damp mop.

Product Details

Code:	LAM-AL-10-005
Brand:	Aqualock
Construction:	Laminate
Surface:	EIR
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	10mm
Width:	158mm
Length:	1285mm
Coverage per pack:	1.624m ²
AC rating:	AC5 Commercial

Warranty

Residential:	25 Years
Commercial:	5 Years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	Water Resistant (Up to 24 Hours)
Technical Class:	33
Fire resistance:	EN 13501-1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN ISO 4892-2
VOC emissions:	A+
Thickness swelling:	EN 13329
Environmental certification	PEFC
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.