



UK FLOORING DIRECT



## Product Data Sheet

LAM-AUTL-12-316

Scan the QR code for fast access to this floor online

## Audacity 12mm Laminate Tile Storm Grey

As striking as lightning and making an entrance like thunder, Audacity 12mm Laminate Tile Storm Grey is here to whip up some opulent and contemporary style in your home. The moody grey tone is the perfect pick to welcome in the darker atmosphere that lends itself so well to creating a luxurious mood for anywhere from your bathroom to your kitchen, and even your living spaces. Creating even more depth and definition with the four bevelled edges adorning each plank, this floor packs just as much practicality as it does style into every board to weather the storm of spills, splashes and even paws that make up life in a busy home.

The extra rigid core of this floor adds in stability that's perfect in the biggest rooms to reduce any chance of movement. And with a DIY-friendly click system and built-in underlay that makes for a quick and easy fit of this floor, there's as much calm before the storm as there is after.

With its easy to care for and stain resistant surface, as well as 72-hour water-resistance, spills and messes can be easily wiped away sparing you from whatever messes your busy home usually troubles you with. And with its AC4 Heavy Domestic rating and lifetime residential warranty, Audacity 12mm Laminate Tile Storm Grey offers true and complete peace of mind.

### Product Details

Code:	LAM-AUTL-12-316
Brand:	Audacity
Construction:	Laminate
Surface:	EIR
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	12mm
Width:	300mm
Length:	600mm
Coverage per pack:	1.62m <sup>2</sup>
AC rating:	AC4 Heavy Domestic

### Warranty

Residential:	Lifetime
Commercial:	5 Years

### Installation

Floated:	Yes
Over underfloor heating:	Yes, Water Systems

### Technical

Water rating:	Water Resistant (Up to 72 hours)
Technical Class:	32
Fire resistance:	Ffl
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	N/A
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 433
Effects of castor chair:	EN 433
Light fastness:	EN 13329
VOC emissions:	A+
Thickness swelling:	EN 13329 / <18%
Environmental certification	EUTR
Tolerance:	N/A

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.