



SERIES FLOORING

UK FLOORING DIRECT



Product Data Sheet

LAM-SE-10-400

Scan the QR code for fast access to this floor online

Series Woods 8mm Acoustic Laminate Arctic White Oak

With light grey tones and understated grain markings, Series Woods 8mm Acoustic Laminate Arctic White Oak has a cool, modern vibe and would make a beautiful backdrop for a contemporary interior scheme. Lead the way with this hardwearing, realistic looking laminate that will be sure to make a statement. The boards have a textured surface that beautifully enhances the wood effect and come in a classic size (197mm x 1220mm) that is perfectly proportioned for making small and medium-length rooms feel more spacious.

An AC4 heavy domestic rating and a 15-year warranty makes this floor suitable for all rooms including areas with heavy traffic.

This floor is fabulous to look at and incredibly easy to care for and install, featuring a DIY friendly click system on an 8mm thick board. With a 2mm integrated underlay, which has 21dB reduction of noise, soundproofing has never been easier. This floor is ideal for busy homes and easy to clean, with regular vacuuming and an occasional damp mop.

Product Details

Code:	LAM-SE-10-400
Brand:	Series Woods
Construction:	Standard HDF
Surface:	Embossed In Register
Profile:	Click System
Edge profile:	Painted Bevel
Thickness:	8mm + 2mm Integrated Underlay
Width:	197mm
Length:	1220mm
Coverage per pack:	2.884m ²
AC rating:	AC4
dB rating:	21dB

Warranty

Residential:	15 years
Commercial:	10 years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

Technical

Water rating:	Water Resistant (Up to 72 Hours)
Technical Class:	Class 32
Fire resistance:	Class BFl-S1
Formaldehyde emission:	Class E1
Slip resistance:	Class DS
Thermal resistance/conductivity:	CE/ max. 0.1 (Km ²)/W
Resistance to staining:	EN 438-2:2019
Wear resistance:	EN16511/ ≥ 4,000 cycles
Effects of furniture leg:	EN 425 / No Effects
Effects of castor chair:	EN 425/≥ 25,000 cycles
Light fastness:	EN 20105/≥ 6 (Slight effect)
VOC emissions:	ISO 16000 CE certificate
Thickness swelling:	EN16511 / ≤ 12%

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG
Tel: 02476 012 840
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2024. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.