



SERIES FLOORING

UK FLOORING DIRECT



Product Data Sheet

LAM-SE-10-401

Scan the QR code for fast access to this floor online

Series Woods 8mm Acoustic Laminate Dove Grey Oak

Series Woods 8mm Acoustic Laminate Dove Grey Oak looks and feels just like a hardwood floor but is more than a match for the rigours of hectic family life. With light grey tones and understated grain markings, this floor has a cool, modern vibe and would make a beautiful backdrop for a contemporary interior scheme.

The boards have a textured surface that beautifully enhances the wood effect and come in a classic size (197mm x 1220mm) that is perfectly proportioned for making small and medium-length rooms feel more spacious.

With a DIY friendly click system on a 8mm thick board including a 2mm integrated underlay, which has 21dB rating means soundproofing your home has just become easier. An AC4 heavy domestic rating and a 15-year warranty this floor is suitable for any room including areas with heavy traffic.

Vacuuming and an occasional damp-mopping is all it takes to keep Series Woods 10mm Laminate Dove Grey Oak looking fantastic, making it a great choice for anyone looking for a low-maintenance fit-and forget floor.

Product Details

| | |
|---------------------------|-------------------------------|
| Code: | LAM-SE-10-401 |
| Brand: | Series Woods |
| Construction: | Standard HDF |
| Surface: | Embossed In Register |
| Profile: | Click System |
| Edge profile: | Painted Bevel |
| Thickness: | 8mm + 2mm Integrated Underlay |
| Width: | 197mm |
| Length: | 1220mm |
| Coverage per pack: | 2.884m ² |
| AC rating: | AC4 |
| dB rating: | 21dB |

Warranty

| | |
|---------------------|----------|
| Residential: | 15 years |
| Commercial: | 10 years |

Installation

| | |
|---------------------------------|---|
| Floated on underlay: | Yes |
| Over underfloor heating: | Yes, Electric & Water Systems up to 27 °C |

Technical

| | |
|---|-----------------------------------|
| Water rating: | Water Resistant (Up to 72 Hours) |
| Technical Class: | Class 32 |
| Fire resistance: | Class BFl-S1 |
| Formaldehyde emission: | Class E1 |
| Slip resistance: | Class DS |
| Thermal resistance/conductivity: | CE/ max. 0.1 (Km ²)/W |
| Resistance to staining: | EN 438-2:2019 |
| Wear resistance: | EN16511/ ≥ 4,000 cycles |
| Effects of furniture leg: | EN 425 / No Effects |
| Effects of castor chair: | EN 425/≥ 25,000 cycles |
| Light fastness: | EN 20105/≥ 6 (Slight effect) |
| VOC emissions: | ISO 16000 CE certificate |
| Thickness swelling: | EN16511 / ≤ 12% |

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QQ
Tel: 02476 012 840
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2024. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.