



SERIES FLOORING

Product Data Sheet

LAM-SE-10-402

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Series Woods 8mm Acoustic Laminate Rhino Grey Oak

Series Woods 8mm Acoustic Laminate Rhino Grey Oak brings a timeless elegance look in any room. This floor is the perfect way to add grounding to a neutral scheme or bring balance to adventurous colours.

This floor features a textured surface that gives the look and feel of wood while remaining hardwearing and easy to look after. The planks come in a classic size (197mm x 1220mm) that is perfectly proportioned for making small and medium-length rooms feel more spacious.

With a DIY friendly click system on a 8mm thick board including a 2mm integrated underlay, which has 21dB rating means soundproofing your home just became easier. An AC4 heavy domestic rating and a 15-year warranty this floor is suitable for any room including areas with heavy traffic.

Vacuuming and an occasional damp-mopping is all it takes to keep Series Woods 10mm Laminate Rhino Grey Oak looking fantastic, making it a great choice for anyone looking for a low-maintenance floor.

Product Details

Code:	LAM-SE-10-402
Brand:	Series Woods
Construction:	Standard HDF
Surface:	Embossed In Register
Profile:	Click System
Edge profile:	Painted Bevel
Thickness:	8mm + 2mm Integrated Underlay
Width:	197mm
Length:	1220mm
Coverage per pack:	2.884m ²
AC rating:	AC4
dB rating:	21dB

Warranty

Residential:	15 years
Commercial:	10 years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

Technical

Water rating:	Water Resistant (Up to 72 Hours)
Technical Class:	Class 32
Fire resistance:	Class BFl-S1
Formaldehyde emission:	Class E1
Slip resistance:	Class DS
Thermal resistance/conductivity:	CE/ max. 0.1 (Km ²)/W
Resistance to staining:	EN 438-2:2019
Wear resistance:	EN16511/ ≥ 4,000 cycles
Effects of furniture leg:	EN 425 / No Effects
Effects of castor chair:	EN 425/≥ 25,000 cycles
Light fastness:	EN 20105/≥ 6 (Slight effect)
VOC emissions:	ISO 16000 CE certificate
Thickness swelling:	EN16511 / ≤ 12%

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG
Tel: 02476 012 840
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2024. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.