



# SERIES FLOORING

UK FLOORING DIRECT



## Product Data Sheet

**LAM-SE-10-404**

Scan the QR code for fast access to this floor online

## Series Woods 8mm Acoustic Laminate Soft Honey Oak

If you're after a low-maintenance floor with the traditional look of real wood and a homely, welcoming vibe, Series Woods 8mm Acoustic Laminate Soft Honey Oak is a great choice. In a versatile natural oak tone that will beautifully complement a wide range of colour schemes, this floor has a textured surface that replicates the feel of genuine oak and comes with all the practical benefits of a quality laminate.

The wide, classic-length boards are a versatile size (197mm x 1220mm) that is particularly well suited to creating a space-enhancing effect in small and medium-length rooms. Featuring a DIY friendly click system on an 8mm thick board including a 2mm integrated underlay, with a 21dB rating means soundproofing your home just became easier.

With an AC4 Heavy Domestic rating, this durable floor is suitable for bedrooms, conservatories, dining rooms, hallways, kitchens, living rooms and utility rooms and comes with a 15-year warranty. Vacuuming and an occasional damp-mopping is all it takes to keep this floor looking fantastic, making it a great choice for anyone looking for a low-maintenance floor.

### Product Details

<b>Code:</b>	LAM-SE-10-404
<b>Brand:</b>	Series Woods
<b>Construction:</b>	Standard HDF
<b>Surface:</b>	Embossed In Register
<b>Profile:</b>	Click System
<b>Edge profile:</b>	Painted Bevel
<b>Thickness:</b>	8mm + 2mm Integrated Underlay
<b>Width:</b>	197mm
<b>Length:</b>	1220mm
<b>Coverage per pack:</b>	2.884m <sup>2</sup>
<b>AC rating:</b>	AC4
<b>dB rating:</b>	21dB

### Warranty

<b>Residential:</b>	15 years
<b>Commercial:</b>	10 years

### Installation

<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes, Electric & Water Systems up to 27 °C

### Technical

<b>Water rating:</b>	Water Resistant (Up to 72 Hours)
<b>Technical Class:</b>	Class 32
<b>Fire resistance:</b>	Class BFl-S1
<b>Formaldehyde emission:</b>	Class E1
<b>Slip resistance:</b>	Class DS
<b>Thermal resistance/conductivity:</b>	CE/ max. 0.1 (Km <sup>2</sup> )/W
<b>Resistance to staining:</b>	EN 438-2:2019
<b>Wear resistance:</b>	EN16511/ ≥ 4,000 cycles
<b>Effects of furniture leg:</b>	EN 425 / No Effects
<b>Effects of castor chair:</b>	EN 425/≥ 25,000 cycles
<b>Light fastness:</b>	EN 20105/≥ 6 (Slight effect)
<b>VOC emissions:</b>	ISO 16000 CE certificate
<b>Thickness swelling:</b>	EN16511 / ≤ 12%

### UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG  
Tel: 02476 012 840  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2024. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.