



# SERIES FLOORING

UK FLOORING DIRECT



## Product Data Sheet

LAM-SE-10-406

Scan the QR code for fast access to this floor online

## Series Woods 8mm Acoustic Laminate Rich Caramel Oak

With rich caramel tones that will make any room feel instantly more welcoming, Series Woods 8mm Acoustic Laminate Rich Caramel Oak delicate grain patterns and a textured surface that beautifully enhance the traditional wood floor look.

The wide, classic-length boards are a versatile size (197mm x 1220mm) that is particularly well suited to creating a space-enhancing effect in small and medium-length rooms.

An AC4 heavy domestic rating and a 15-year warranty makes this floor suitable for all rooms including areas with heavy traffic.

This floor is fabulous to look at and incredibly easy to care for and install, featuring a DIY friendly click system on an 8mm thick board. With a 2mm integrated underlay, which has 21dB reduction of noise, soundproofing has never been easier. This floor is ideal for busy homes and easy to clean, with regular vacuuming and an occasional damp mop.

### Product Details

Code:	LAM-SE-10-406
Brand:	Series Woods
Construction:	Standard HDF
Surface:	Embossed In Register
Profile:	Click System
Edge profile:	Painted Bevel
Thickness:	8mm + 2mm Integrated Underlay
Width:	197mm
Length:	1220mm
Coverage per pack:	2.884m <sup>2</sup>
AC rating:	AC4
dB rating:	21dB

### Warranty

Residential:	15 years
Commercial:	10 years

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

### Technical

Water rating:	Water Resistant (Up to 72 Hours)
Technical Class:	Class 32
Fire resistance:	Class BF1-S1
Formaldehyde emission:	Class E1
Slip resistance:	Class DS
Thermal resistance/conductivity:	CE/ max. 0.1 (Km <sup>2</sup> )/W
Resistance to staining:	EN 438-2:2019
Wear resistance:	EN16511/ ≥ 4,000 cycles
Effects of furniture leg:	EN 425 / No Effects
Effects of castor chair:	EN 425/≥ 25,000 cycles
Light fastness:	EN 20105/≥ 6 (Slight effect)
VOC emissions:	ISO 16000 CE certificate
Thickness swelling:	EN16511 / ≤ 12%

### UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG  
Tel: 02476 012 840  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2024. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.