





Product Data Sheet LAM-SE-12-030



Scan the QR code for fast access to this floor online

Series Woods 12mm Laminate Flooring Mist Oak

Series Woods 12mm Laminate Flooring Mist Oak looks and feels just like a real wood floor but is more than a match for the rigours of a busy home. With light grey tones and understated grain markings, Mist Oak Laminate has a cool, modern vibe and would make a beautiful backdrop for a contemporary interior scheme. At 12mm thick, with an AC4 rating, this durable floor is suitable for most rooms, including bedrooms, conservatories and dining rooms.

The wide, classic-length boards are textured for an authentic real wood look and feel and come in a versatile size (192mm x 1285mm) that is particularly well suited to creating a space-enhancing effect in small and medium-length rooms. A click fitting system, with joints on all four sides of each board, makes DIY installation fast and easy.

Product Details

| Code: | LAM-SE-12-030 |
|--------------------|----------------------|
| Brand: | Series Woods |
| Construction: | Laminate |
| Surface: | EIR |
| Profile: | Click |
| Edge profile: | Bevelled on 4 sides |
| Thickness: | 12mm |
| Width: | 192mm |
| Length: | 1285mm |
| Coverage per pack: | 1.48 |
| AC rating: | AC4 - Heavy Domestic |

Warranty

| Residential: | 20 years |
|--------------|----------|
| Commercial: | 5 years |

Installation

| Floated on underlay: | Yes |
|--------------------------|--------------------------------|
| Over underfloor heating: | Yes, up to a max of 27 degrees |

Technical

| Water rating: | Splashproof |
|----------------------------------|---|
| Technical Class: | 23/32 |
| Fire resistance: | EFL |
| Formaldehyde emission: | El |
| Slip resistance: | DS |
| Thermal resistance/conductivity: | R23 / ≤ 0.1 (m_K)/W |
| Resistance to staining: | EN 438.2.15 / Group 1, 2:5 and Group 3:4 |
| Wear resistance: | EN 13329 |
| Effects of furniture leg: | EN 13329 |
| Effects of castor chair: | EN 13329 |
| Light fastness: | EN 20105-B02 |
| VOC emissions: | A+ |
| Thickness swelling: | EN 13329 / <18% |
| Tolerance: | EN 13329 |

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ Tel: 02476 012840 | Fax: 02476 397828 info@ukflooringdirect.co.uk ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.