



Product Data Sheet

LAM-SE-12-364

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Series Woods Professional 12mm Laminate Flooring Galley Oak

Offer up a warm welcome in any room with Series Woods Professional 12mm Laminate Flooring Galley Oak. The gorgeous natural tones of this wood-effect floor bring a traditional-style beauty that still packs in every benefit of modern laminate construction — from the four bevelled edges of each plank that give the finished floor more depth and definition to the characterful grain pattern that rests beneath an embossed in register texture to add a touch of elegance.

A favourite of DIYers, novice and experts alike, thanks to the innovative click-together joint system that makes fitting fast and easy for everyone. At 12mm thick, the 1285mm x 192mm boards are perfect all-rounders and especially handy in medium-length rooms for creating a classic, space-enhancing look.

Not content with just offering you splendid natural style, Series Woods Professional 12mm Laminate Flooring Galley Oak packs just as much performance on to each board with an AC5 Commercial rating and 30-year warranty, offering you complete peace of mind. Maintaining this floor is just as much of a breeze as all this durability should promise — just vacuum regularly and damp mop from time to time to keep it shining on.

Product Details

Code:	LAM-SE-12-364
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	EIR
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	12mm
Width:	192mm
Length:	1285mm
Coverage per pack:	1.48m ²
AC rating:	AC5 Commercial

Warranty

Residential:	30 Years

Commercial:

5 Years

Yes

Installation

Floated on underlay:

Over underfloor heating:

Yes, up to a max of 27°C

Technical

Water rating:	Splash-proof
Technical Class:	23/32
Fire resistance:	Class CfL – S1
Formaldehyde emission:	El
Slip resistance:	DS
Thermal resistance/conductivity:	R23 / ≤ 0.1 (m_K)/W
Resistance to staining:	EN 13329
Wear resistance:	EN 13329
Effects of furniture leg:	EN 13329
Effects of castor chair:	EN 13329
Light fastness:	EN 20105-B02
VOC emissions:	A+
Thickness swelling:	EN 13329
Environmental certification	FSC
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ Tel: 02476 012840 | Fax: 02476 397828 info@ukflooringdirect.co.uk ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.