



SERIES FLOORING

UK FLOORING DIRECT



Product Data Sheet

LAM-SE-9-420

Scan the QR code for fast access to this floor online

Series Woods 7mm Acoustic Laminate Glacier Grey Oak

Series Woods 7mm Acoustic Laminate Flooring Glacier Grey Oak looks and feels just like a hardwood floor, and the cool grey tone will give a modern vibe to any room making a beautiful backdrop for a contemporary interior scheme.

The boards have a textured surface that beautifully enhances the wood effect and comes in a classic size (197mm x 1220mm) that is perfectly proportioned for making small and medium-length rooms feel more spacious.

This floor features a DIY friendly click system on a 7mm thick board with a 2mm integrated underlay, making this floor even easier to fit. This acoustic laminate floor is ideal for busy homes, if your looking for a soundproofing further the integrated underlay has a 21dB reduction of noise.

Series Woods 7mm Acoustic Laminate Glacier Grey Oak has an AC3 Domestic rating making it suitable for hallways, kitchens, bedrooms, dining rooms, living rooms, conservatories, and utility rooms, and only requires regular vacuuming and an occasional damp mopping to stay looking its best.

Product Details

Code:	LAM-SE-9-420
Brand:	Series Woods
Construction:	Standard HDF
Surface:	Authentic Texture
Profile:	Click System
Edge profile:	Panted Bevel
Thickness:	7mm + 2mm Integrated Underlay
Width:	197mm
Length:	1220mm
Coverage per pack:	3.365m ²
AC rating:	AC3
dB rating:	21dB

Warranty

Residential:	10 Years
Commercial:	5 Years

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

Technical

Water rating:	Water Resistant (Up to 24 Hours)
Technical Class:	Class 23 / Class 31
Fire resistance:	Class Bfl-s1
Formaldehyde emission:	Class E1
Slip resistance:	Class DS
Thermal resistance/conductivity:	CE/ max. 0.1 (Km ²)/W
Resistance to staining:	Rating 5/EN 438
Wear resistance:	EN16511/ ≥ 2,000 cycles
Effects of furniture leg:	EN 425 / No Effects
Effects of castor chair:	EN 425/≥ 25,000 cycles
Light fastness:	EN 20105/≥ 6 (Slight effect)
VOC emissions:	ISO 16000 CE certificate
Tolerance:	EN16511 / ≤ 12%

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG
Tel: 02476 012 840

info@ukflooringdirect.co.uk

ukflooringdirect.co.uk

© 2024. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.