

# UK Flooring Direct

## Engineered Click Installation Guide

### Engineered Click

---

### Installation Guide

Engineered floors are very dimensionally stable allowing them to be installed over all types of sub floors. They are suitable for all areas of the house except bathrooms and wet areas. They are also suitable for use over under floor heating and conservatories.

### Engineered Click

---

### Storage

Decorating and remodelling a home is a time-consuming process that can become even longer when little problems arise. If your building project exceeds the original timeframe you may need to store some of your flooring materials like Engineered Wood flooring. Engineered Wood flooring is susceptible to environmental damage so it must be stored properly in order for it to be viable for use when you need it. If you make the effort to store your flooring properly, you can avoid having to deal with damage or replacements later.

While it may be required to leave Engineered Wood flooring in the garage for a few days before bringing it inside to acclimatise, these conditions are not acceptable for long-term storage. Flooring must be kept in properly enclosed surroundings that have a secure roof and weatherproof windows. Extreme temperatures and excess moisture can irreparably damage wood flooring so it is important to select an area that will protect your flooring from exposure to the elements.

If Engineered Wood flooring is exposed to freezing temperatures or extreme heat, this can lead to cracking or warping. In order to prevent this damage, if you are not sure, speak to our Customer Sales Team about what temperature and humidity is ideal for storing your particular type of flooring, and do what you can to control the temperature and humidity in your temporary storage area. Engineered Wood flooring needs to be kept clean and dry, so



Perfect Flooring. In one easy step.  
[www.ukflooringdirect.co.uk](http://www.ukflooringdirect.co.uk)

# UK Flooring Direct

## Engineered Click Installation Guide

air circulation is also a concern. Clean air should be allowed to circulate among the stacks of flooring; you may need to install fans if your building has poor air flow.

The flooring should be laid down horizontally onto a flat surface, and never propped up against a wall, for example, as this is likely to cause the flooring to warp and bow.

As a general guide, look at Temperatures in the region of 18-24°C and Relative Humidity 45-60%. (Please refer to the manufactures guides upon delivery, or if you anticipate storage needs contact our Customer Service Team on 08443 274 444)

## Engineered Click

---

### Acclimatisation

Due to their stability they can be fitted in a minimum of 48 hours after correctly being acclimatised. To correctly acclimatise your engineered floor it should be left in the room it is going to be fitted in at suitable room temperature and relative humidity (RH). Please refer to the manufactures guides contained within the packaging for accurate advice of your chosen product.



Perfect Flooring. In one easy step.  
[www.ukflooringdirect.co.uk](http://www.ukflooringdirect.co.uk)

# UK Flooring Direct

## Engineered Click Installation Guide

### Engineered Click Installation

---

Engineered flooring with a click installation system can be installed as floating floor, which is the most common and DIY friendly installation method because it is the easiest and the fastest to install. They can be installed over any type of subfloor and do not require any special skills or prior experience in installing floors as the floors just clicks together with no need for any glue.

All floating flooring installations must use the correct underlay. Over a concrete subfloor you will need to use a superior underlay which has a built in damp proof membrane (DPM) such as Cushion Premium Black Underlay. Over a wooden subfloor you can use the Cushion Standard White Underlay or Cushion Plus White Underlay with its vapour barrier that allow the flooring and subfloor to breath. For installations over under floor heating we recommend using Cushion Ultra Silver underlay. Also for improved noise reduction we recommend the Cushion Acoustic Gold Underlay, bringing peace and quiet to the room, by reducing “Drum Sound”.

Using the correct underlay can give better support to your new flooring, which in turn prolongs the life and also aids installation by removing some minor imperfections from the sub-floor.

Each board is designed with a click profile on all four sides to join the boards together. Simply insert the long side tongue into the groove at around a 30° angle and then push them down. The shorter end, known as the “Header Joint”, will vary dependent on product chosen. You will need to refer to the manufactures guides for further product specific instructions.

You will need to leave a minimum 15mm expansion gap around the perimeter of the room. To maintain this gap during installation spacers are provided in our installation kit (purchased separately).



Perfect Flooring. In one easy step.  
[www.ukflooringdirect.co.uk](http://www.ukflooringdirect.co.uk)

# UK Flooring Direct

## Engineered Click Installation Guide

After you have installed the floor you can cover this expansion gap with scotia beading or replace you old skirting boards with new ones; this gives a much more professional finish. An expansion gap also needs to be left in doorways where the floor follows through from one room to another or not. We have a full range of door profiles available to match your floor.

This is a brief guideline on the installation of our click engineered flooring; always refer to the manufactures installation guidelines contained within packs of the flooring or visit our Flooring Manufacture Installation Guides.

**If you require any further advice on installation then please call our technical department on 0844 327 5555, e-mail us on [technical@ukflooringdirect.co.uk](mailto:technical@ukflooringdirect.co.uk).**



Perfect Flooring. In one easy step.

**[www.ukflooringdirect.co.uk](http://www.ukflooringdirect.co.uk)**