



UK FLOORING DIRECT



## Product Data Sheet

**VIN-CLIC-PL-429**

Scan the QR code for fast access to this floor online

## ParquetVinyl Colorado Rapids Plank Luxury Rigid Core Click Vinyl Flooring

With the characterful look of fumed oak, ParquetVinyl Colorado Rapids Plank Luxury Click Vinyl will bring a touch of vintage style to any room while offering all the practical benefits of rigid core vinyl.

Featuring an Authentic Textured surface that follows the wood grain and surface markings of the décor layer and bevelled edges for the best in realism, this style comes in a wide (176mm), classic length (1213mm) plank that makes it incredibly versatile. Thanks to a stable rigid core, ParquetVinyl is less likely to indent and mark, its water-resistant construction and highly-durable, simple to maintain surface making ParquetVinyl Colorado Rapids Plank Luxury Click Vinyl Flooring ready for any situation.

Coming with a 35-year residential warranty this is one tough floor, achieving an AC 5 commercial wear rating for complete peace of mind. Fast-to-fit, thanks to a DIY click joint and rigid construction that just needs a flat subfloor, ParquetVinyl Colorado Rapids Plank Luxury Click Vinyl Flooring is so stable it's safe to use with underfloor heating or in areas exposed to changes in humidity and temperature. UV-resistant too, it's great for use in conservatories.

### Product Details

Code:	VIN-CLIC-PL-429
Brand:	ParquetVinyl
Construction:	SPC
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Wear layer:	0.55mm
Thickness:	4mm
Width:	176mm
Length:	1213mm
Coverage per pack:	2.56m <sup>2</sup>
AC rating:	AC5 - Commercial

### Warranty

Residential:	35 Year
Commercial:	20 Years

NB: Please ask for full warranty terms and conditions

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

### Technical

Water rating:	Waterproof
Technical Class:	Class 33
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	EN 13893
Thermal resistance/conductivity:	EN 14041
Resistance to staining:	EN 14041
Wear resistance:	EN 14041

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.