



Product Data Sheet VIN-CLIC-PL-829





Scan the QR code for fast access to this floor online

Spectra Steel Oak Plank Luxury Rigid Core Click Vinyl Flooring

When it comes to our floors, we should not have to choose between a timeless look everyone is envious of, perfectly on-trend tones that meld with a variety of styles, or functional filled with benefits that enhance our home and our lives. Spectra Steel Oak Plank packs all of this into one stylish package that performs such a well realised imitation of real wood that you'll be hard pressed to notice the difference - with authentic grain and texture that help elevate the effect of the finished floor alongside the four bevelled edges and the wide planks that reach 1.3m in length. This floor also comes complete with an attached underlay so that's one less thing for you to think about.

There are also plenty of benefits to be found under the waterproof surface - from the unique polyurethane layer that protects against stains and keeps your floor looking its best, to the AC5 rating and 20-year residential warranty that gives you plenty of peace of mind, to the DIY-friendly click system technology that makes installation easy for everyone.

Product Details

Code:

| couc. | VIIV CEIC I E 025 |
|--------------------|-------------------------------|
| Brand: | Spectra |
| Construction: | Rigid Core (EVF) |
| Surface: | Authentic Textured |
| Profile: | Click System |
| Edge profile: | Bevelled on 4 sides |
| Thickness: | 5mm + 1mm Integrated Underlay |
| Width: | 189mm |
| Length: | 1317mm |
| Coverage per pack: | 1.99 |
| AC rating: | AC5 - Commercial |
| Wear Layer: | 0.55mm |

VIN-CLIC-PL-829

Technical

| Water rating: | Waterproof |
|----------------------------------|---|
| Technical Class: | 23-33 |
| Fire resistance: | Bfl-S1 |
| Formaldehyde emission: | El |
| Slip resistance: | DS R10 |
| Thermal resistance/conductivity: | EN 12667 |
| Resistance to staining: | EN ISO 26987 |
| Wear resistance: | EN ISO 10874 |
| Effects of furniture leg: | EN ISO 16581 No cracks, or damage |
| Effects of castor chair: | EN ISO 4918 No damage to wearlayer, no delamination |
| Light fastness: | EN ISO 105-B02 ≥6 |

Warranty

| Residential: | 20 years |
|--------------|----------|
| Commercial: | 10 years |

Installation

Floated on underlay: No Over underfloor heating: Yes, Water Systems up to 27°C

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ Tel: 02476 012840 | Fax: 02476 397828 info@ukflooringdirect.co.uk ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.