



# LiFE

## VINYL

UK **FLOORING** DIRECT



Scan the QR code for fast access to this floor online

### Product Data Sheet

#### VIN-CLIC-PL-866

## Life Mocha Oak Herringbone Luxury Rigid Core Click Vinyl Flooring

If you're looking for a wood-effect floor with a difference, then Life Mocha Oak Herringbone Luxury Rigid Core Click Vinyl has that difference – rich tones of roasted coffee and smooth caramel that blend in the grain to create this one-of-a-kind look for this incredible floor. The benefits of rigid core vinyl, also known as Stone Plastic Composite or SPC, make this floor even more irresistible with fantastic durability worthy of an AC5 rating and a 70% limestone core. All this makes this floor ideal for not only the busiest of homes, but even commercial settings.

This floor also makes use of a click fitting system, easy for even amateur DIYers to install without needing any glue or nails, just underlay.

Being 100% waterproof and suitable for underfloor heating systems up to 27°C means it can be installed in any room in the home, including kitchens and bathrooms, and can withstand surface temperatures up to 60°C making it perfect for conservatories. At 615mm x 123mm, the planks are ideally sized for the herringbone pattern, adding space into a room along with a timeless appeal.

### Product Details

Code:	VIN-CLIC-PL-866
Brand:	Life
Construction:	Rigid Core (SPC)
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Painted
Thickness:	4mm
Width:	123mm
Length:	615mm
Coverage per pack:	2.12
AC rating:	AC5 - Commercial
Wear Layer:	0.55mm

### Warranty

Residential:	Lifetime
Commercial:	15 years

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

### Technical

Water rating:	Waterproof
Technical Class:	33
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	R10
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	No visible damage
Effects of castor chair:	NA
Light fastness:	_E ≤8
VOC emissions:	GGG certified
Thickness swelling:	_ 12%
Tolerance:	≤0.10% (width) 0.5mm (length) +0.13mm/-0.1mm (thickness)

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.