





Product Data Sheet VIN-CLIC-TL-442



Scan the QR code for fast access to this floor online

Spectra Dove Grey Stone Tile Luxury Click Vinyl Flooring

Modern and pared-back with a cool industrial vibe, grey floors have never been more popular. If you love the look of concrete and grey stone but want all the practical benefits that the latest LVT floors can bring, Spectra Dove Grey Stone Tile Luxury Click Vinyl Flooring could be the ideal choice for you.

With a warm mid-grey tone and a streamlined appearance, this hardwearing floor features an authentic textured surface and a softly mottled décor layer that add realism to its polished concrete look. Compatible with underfloor heating and fully waterproof, it's safe for use in demanding areas such as kitchens, utility rooms and bathrooms, and comes in fixed-size large tiles (299mm x 604.6mm) with micro-bevelled edges that work well in any size of room and ensure a clean, contemporary finish.

Spectra Dove Grey Stone Tile Luxury Click Vinyl Flooring will more than earn its keep in a busy family home. Regular vacuuming and occasional damp mopping are all it takes to maintain its good looks, while a patented click system ensures it's fast and easy to fit, even for DIYers.

Product Details

Code:	VIN-CLIC-TL-442
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Click System
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	4.2mm
Width:	299mm
Length:	604.6mm
Coverage per pack:	1.99m ²
AC rating:	AC3 - Domestic

Warranty

Residential:	12 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded.

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	El
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ Tel: 02476 012840 | Fax: 02476 397828 info@ukflooringdirect.co.uk ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.