



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-TL-450

Scan the QR code for fast access to this floor online

Spectra Timeless Grey Stone Tile Luxury Click Vinyl Flooring

The ultimate in industrial chic, grey stone flooring will never go out of fashion. If you're looking for a modern style that won't date, Spectra Timeless Grey Stone Tile Luxury Click Vinyl Flooring could be ideal.

In a versatile mid-grey hue that will tone with a huge range of colour schemes, this family-friendly floor boasts an authentic textured surface and a softly mottled décor layer that add realism to its stone look. Compatible with underfloor heating and fully waterproof, it's safe for use in demanding areas such as kitchens, utility rooms and bathrooms, and comes in fixed-size large (324mm x 655mm) tiles with micro-bevelled edges that work well in any size of room and ensure a clean, contemporary finish.

Spectra Timeless Grey Stone Tile Luxury Click Vinyl Flooring will more than earn its keep in a busy family home. Regular vacuuming and occasional damp mopping are all it takes to maintain its good looks, while a patented click system ensures it's fast and easy to fit, even for DIYers.

Product Details

Code:	VIN-CLIC-TL-450
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Click System
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	4.5mm
Width:	324mm
Length:	655mm
Coverage per pack:	1.49m ²
AC rating:	AC3 - Domestic

Warranty

Residential:	12 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.