





# Product Data Sheet VIN-CLIC-TL-467



Scan the QR code for fast access to this floor online

## Spectra Light Grey Cement Tile Luxury Click Vinyl Flooring

Modern and pared-back with a cool industrial vibe, grey floors have never been more popular. If you love the look of concrete but want all the practical benefits that the latest LVT floors can bring, Spectra Light Grey Cement Tile Luxury Click Vinyl Flooring could be the ideal choice for you.

With a cool mid-grey tone and a streamlined appearance, this hardwearing floor features an authentic textured surface and a softly mottled décor layer that adds realism to its concrete look. Compatible with underfloor heating and fully waterproof, it's safe for use in demanding areas such as kitchens, utility rooms and bathrooms, and comes in bevel-edged uniform large (324mm x 655mm) tiles that work well in any size of room.

Coming with a 20-year warranty, Spectra Light Grey Cement Tile Luxury Click Vinyl Flooring will more than earn its keep in a busy family home. Regular vacuuming and occasional damp mopping are all it takes to maintain its good looks, while a patented click system ensures it's fast and easy to fit, even for DIYers.

#### **Product Details**

Code:	VIN-CLIC-TL-467
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Wear layer:	0.55mm
Thickness:	4.5mm
Width:	324mm
Length:	655mm
Coverage per pack:	1.49m²
AC rating:	AC5 - Commercial

#### Warranty

Residential:	20 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

## Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

### **Technical**

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	El
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

## **UK Flooring Direct**

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ Tel: 02476 012840 | Fax: 02476 397828 info@ukflooringdirect.co.uk ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.