



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-DRY-PL-485

Scan the QR code for fast access to this floor online

Spectra Sea Salt Oak Plank Luxury Glue Down Vinyl Flooring

Clean, elegant and understated, Spectra Sea Salt Oak Plank Luxury Glue Down Vinyl boasts beautiful snowy tones and the subtlest of grain patterns, making it an ideal backdrop for contemporary and minimalist interior schemes.

This modern LVT floor is designed to withstand the rigours of family life; waterproof, hard-wearing and easy to clean. It can safely be used in demanding areas such as bathrooms, hallways and kitchens, as well as living spaces and bedrooms.

Enhanced with an authentic textured surface for a realistic oak look and feel, Spectra Sea Salt Oak Plank Luxury Glue Down Vinyl Flooring comes in a uniform size (196mm x 1320mm) – ideal for balancing the proportions of small and medium rooms.

A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting. This is a fantastically low-maintenance option for busy spaces; regular vacuuming and occasional damp mopping are all it takes to keep looking its best.

Product Details

Code:	VIN-DRY-PL-485
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Glue Down/Dry Back
Edge profile:	Micro Bevel
Wear layer:	0.55mm
Thickness:	2.5mm
Width:	196mm
Length:	1320mm
Coverage per pack:	3.62m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	20 Years
Commercial:	10 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Fully bonded:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.