



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-DRY-PL-491

Scan the QR code for fast access to this floor online

Spectra Fossil Oak Plank Luxury Glue Down Vinyl Flooring

With an on-trend sandy hue, hints of grey and a relaxed grain – complete with occasional cracks and swirls – Spectra Fossil Oak Plank Luxury Glue Down Vinyl Flooring is a great choice. Especially if you want to bring a laid-back modern vibe into your living space.

This family-friendly LVT floor has an authentic textured surface that enhances the oak look and is fully waterproof so you can use it in demanding areas such as hallways, kitchens and bathrooms without worry. Its planks are a uniform, classic size (196mm x 1320mm) ideal for use in small and medium rooms, where they'll help create a feeling of space.

Boasting a 20-year residential warranty, Spectra Fossil Oak Plank Luxury Glue Down Vinyl is best fitted by a professional or a keen D.I.Yer with experience using adhesive, to offer enhanced durability and resilience against any unwanted shifting. It is a fantastically low-maintenance option for busy spaces; simply vacuum regularly and clean occasionally with a damp mop.

Product Details

Code:	VIN-DRY-PL-491
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Glue Down/Dry back
Edge profile:	Micro Bevel
Wear layer:	0.55mm
Thickness:	2.5mm
Width:	196mm
Length:	1320mm
Coverage per pack:	3.62m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	20 Years
Commercial:	10 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Fully bonded:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.