

# HOME CHOICE

## CARPETS

### Product Data Sheet

### CAR-CHI-SSG



Scan the QR code for fast access to this floor online

## Home Choice Chicago Stage Grey Stripe Loop Pile Wool Carpet 7mm

Look no further than our Home Choice Chicago range if sumptuous style paired with incredible reliability is what you're after. Crafted from 100% premium fine wool yarn which makes for a great resistant flooring, ideal for most rooms in your home, from your lounge to your hallway. Its resistance is only heightened with its sturdy and hard-wearing action backing. With a toasty 1.4 TOG rating and loop pile, you'll be kept warm from head to toe as this carpet boasts sound and heat insulation. Available in a 4m or 5m width, this carpet can be cut to any length based on your individual requirements.

Make your whole home a stage with our brilliantly new striped wool carpet. Chicago Stage blends darker grey and brown tones with lighter beige stripes to provide a design that you'll be excited to show off. Thanks to the 3-ply build of the range, the light and flexible fabric provides a comfortable feel underfoot. The perfect pairing for both a contemporary and traditional designs, this floor will easily fit any home.

### Product Details

<b>Code:</b>	CAR-CHI-SSG
<b>Brand:</b>	Home Choice
<b>Construction:</b>	Loop
<b>Material:</b>	100% Wool
<b>Pile Height (mm):</b>	5
<b>Thickness:</b>	7mm
<b>Ply:</b>	3-Ply
<b>Backing:</b>	Action
<b>Suitability:</b>	Living Room, Bedroom, Hallway, Stairs, Dining Room, Home Office
<b>Moth Protection:</b>	Yes
<b>Stain Protection:</b>	Resistant to some substances, treat with care
<b>Over floor heating:</b>	Yes, Water Systems up to 27°C and check with the manufacturer before installation

### Warranty

<b>Residential:</b>	7 years
---------------------	---------

### Technical

<b>Gauge:</b>	1/10th
<b>Tog:</b>	1.4
<b>Technical Class:</b>	Class 23 Heavy Domestic, Class 32 General Commercial
<b>Fire Classification:</b>	PASS
<b>Hot metal nut test:</b>	N/A
<b>Pile Weight:</b>	820
<b>Tuft per m2:</b>	N/A
<b>Underlay Recommendation:</b>	Minimum 8mm underlay recommended

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
 Tel: 02476 012840 | Fax: 02476 397828  
 info@ukflooringdirect.co.uk  
 ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.