



GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



Product Data Sheet

ENG-GA-15-132

Scan the QR code for fast access to this floor online

Galleria Professional Engineered European Rustic Oak Flooring 15mm X 190mm Stoney Grey Oiled

With its cool grey tones and eye-catching grain markings, Galleria Professional Engineered European Rustic Oak Flooring 15mm X 190mm Stoney Grey Oiled is ideal for homeowners seeking a fantastic-looking oak floor with a distinctly contemporary feel.

Made from quality European oak in a rustic grade characterised by lively grain patterns, small mineral streaks, sapwood and multiple knots, the boards have been sanded smooth for a clean, modern look and feel, finished with several layers of oil for a natural appearance that's durable enough for busy family living. The tongue-and-groove wide, long-length boards (190mm x 1900mm) work in harmony with spacious interiors, adding an elegant touch and helping to balance the proportions of longer rooms.

With a multi-layer construction for extra stability and topped with a 4mm real oak wear layer that can be sanded and refinished multiple times over the course of its lifetime, this floor defines contemporary living and needs only vacuuming and occasional damp mopping to look its best. For optimum results, professional fitting is recommended.

Product Details

Code:	ENG-GA-15-132
Brand:	Galleria Professional
Construction:	Engineered Multi-Ply
Species:	Oak
Grade:	Rustic
Design:	Plank
Surface:	Smooth
Finish:	Oiled
Profile:	Tongue & Groove
Edge profile:	Bevelled on 4 sides
Top layer:	4mm
Core:	Softwood
Thickness:	15mm
Width:	190mm
Length:	1900mm
Coverage per pack:	2.17m ²

Warranty

Residential:	N/A
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Fully-bonded:	Yes
Nailed:	Yes
Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Max side of sound knots:	50mm diameter
Max size of broken knots:	Unlimited
Sapwood:	Acceptable up to 20% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 3mm wide & 150mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.