



# GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



## Product Data Sheet

**ENG-GA-15-140**

Scan the QR code for fast access to this floor online

## Galleria Professional Engineered European Rustic Oak Flooring 15mm x 190mm Toasted Sesame Oiled

With a warm natural colour and a grain highlighted by lighter tones, this is an engineered wood floor that sets a welcoming and inviting mood making it a great addition to classically styled homes. Galleria Professional Engineered European Rustic Oak Flooring 15mm x 190mm Toasted Sesame Oiled is made from quality European oak using a rustic grade featuring knots, sapwood, mineral streaks and colour variation for a floor that's rich in organic appeal.

Sanded smooth for a clean, modern look and UV oiled for a natural matt finish, the floor comes in a long (1900mm), wide (190mm) plank that works best in large rooms. A bevel on all four edges adds definition and gives a classic wood floor. Featuring an engineered wood three-ply construction that's great value, Galleria Professional Engineered European Rustic Oak Flooring 15mm x 190mm Toasted Sesame Oiled comes with a lasting 4mm wear layer.

With occasional vacuuming and damp mopping, this style will continue to look good. A traditional T&G joint means that gluing or nailing to ensure a secure joint and so this floor is best for professional installation.

### Product Details

<b>Code:</b>	ENG-GA-15-140
<b>Brand:</b>	Galleria Professional
<b>Construction:</b>	Engineered 3-Ply
<b>Species:</b>	Oak
<b>Grade:</b>	Rustic
<b>Design:</b>	Plank
<b>Surface:</b>	Smooth
<b>Finish:</b>	UV Oiled
<b>Profile:</b>	Tongue & Groove
<b>Edge profile:</b>	Bevelled on 4 sides
<b>Top layer:</b>	4mm
<b>Core:</b>	Softwood
<b>Thickness:</b>	15mm
<b>Width:</b>	190mm
<b>Length:</b>	1900mm
<b>Coverage per pack:</b>	2.17m <sup>2</sup>

### Warranty

<b>Residential:</b>	N/A
<b>Commercial:</b>	N/A

NB: Please ask for full warranty terms and conditions

### Installation

<b>Fully-bonded:</b>	Yes
<b>Nailed:</b>	Yes
<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes, Water Systems up to 27 °C

### Technical

<b>Max side of sound knots:</b>	50mm diameter
<b>Max size of broken knots:</b>	Unlimited
<b>Sapwood:</b>	Acceptable up to 20% of the board
<b>Filler &amp; colour variation:</b>	Allowed
<b>Small cracks:</b>	Acceptable up to 3mm wide & 150mm long
<b>Inner bark:</b>	Allowed
<b>Origin of timber:</b>	Europe
<b>Responsible certification:</b>	N/A
<b>Janka hardness rating:</b>	1360

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.