



# GALLERIA

PROFESSIONAL

UK **FLOORING DIRECT**



## Product Data Sheet

**ENG-GA-15-148**

Scan the QR code for fast access to this floor online

## Galleria Professional Engineered Select Oak Chevron Flooring Natural Brushed & Oiled

The classic look of a chevron pattern married to the gorgeous warming tone of a natural wooden floor creates the truly elegant Galleria Professional Engineered Select Oak Chevron Natural Brushed & Oiled. The clean veneer of the select grain, which has minimal sapwood and only a few small knots, creates an unbeatable look that's lifted by the brushed finish. A premium oil finish gives this beautiful floor a truly natural look that will suit a wide range of interior styles. Simply vacuuming and an occasional damp-mop are all that is needed to maintain this floor.

The slim 110mm wide and modest length planks are perfect for creating a cosy feeling in any space, looking their best in small rooms.

The high-quality multi-layer construction of this floor offers exceptional stability, with 3mm hardwood wear layer complimenting the thick boards for a dense underfoot feel. The traditional tongue-and-groove fixing of this floor is best fitted by a professional installer.

### Product Details

<b>Code:</b>	ENG-GA-15-148
<b>Brand:</b>	Galleria Professional
<b>Construction:</b>	Engineered Multi-Ply
<b>Species:</b>	Oak
<b>Grade:</b>	Select
<b>Design:</b>	Plank
<b>Colour:</b>	Naturals
<b>Surface:</b>	Brushed
<b>Finish:</b>	Brushed & Oiled
<b>Profile:</b>	Tongue & Groove
<b>Edge Profile:</b>	Micro Bevel
<b>Top Layer:</b>	3mm
<b>Thickness:</b>	15mm
<b>Width:</b>	110mm
<b>Length:</b>	500mm
<b>Coverage Per Pack:</b>	0.88

### Warranty

<b>Residential:</b>	N/A
<b>Commercial:</b>	N/A

NB: Please ask for full warranty terms and conditions

### Installation

<b>Fully-Bonded:</b>	Yes
<b>Nailed:</b>	Yes
<b>Floated on Underlay:</b>	Yes
<b>Over Underfloor Heating:</b>	Yes, Water Systems up to 27 °C

### Technical

<b>Max Size of Sound Knots:</b>	30mm in diameter
<b>Max size of Broken Knots:</b>	30mm in diameter
<b>Sapwood:</b>	Acceptable up to 30% of the board
<b>Filler &amp; Colour Variation:</b>	Allowed
<b>Layers of Lacquer/Oil:</b>	4
<b>Small Cracks:</b>	Acceptable up to 4mm wide & 100mm long
<b>Inner Bark:</b>	Allowed
<b>Origin of Timber:</b>	Europe
<b>Responsible Certification:</b>	EUTR

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.