



GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



Product Data Sheet

ENG-GA-15-151

Scan the QR code for fast access to this floor online

Galleria Professional Engineered Select Oak Chevron Flooring 15mm x 110mm Marzipan Lacquered

If you're looking to install a stunning real wood floor, then look no further than our Galleria Professional Engineered Wood flooring. Offering exceptional stability, the floor features a high-quality multi-layer construction of several layers of plywood topped with a 3mm hardwood wear layer for a dense feel underfoot and optimum grain definition. With a traditional tongue-and-groove fixing, this load-bearing floor requires professional installation for best results. Keep cosy all year round as this flooring is perfectly suitable with underfloor electric and water heating systems up to 27°C.

Our Galleria Professional Engineered Select Oak Chevron Flooring brings light shades of oak into the home with natural tonal differences and a striking chevron effect pattern that creates an eye-catching look. The clean veneer of the select grain, which has minimal sapwood and only a few small knots, creates an unbeatable look that's lifted by the brushed finish. A premium UV lacquered finish gives this beautiful parquet floor a truly natural look that will suit a wide range of interior styles. Simply vacuuming and an occasional damp mop is all that is needed to keep it looking its best.

Product Details

| | |
|--------------------|-----------------------|
| Code: | ENG-GA-15-151 |
| Brand: | Galleria Professional |
| Construction: | Engineered Multi-Ply |
| Surface: | Brushed |
| Profile: | Tongue & Groove |
| Edge profile: | Bevelled on 4 sides |
| Thickness: | 15mm |
| Width: | 110mm |
| Length: | 500mm |
| Coverage per pack: | 0.88m ² |

Installation

| | |
|--------------------------|---|
| Fully bonded: | Yes |
| Floated on underlay: | No |
| Over underfloor heating: | Yes, Electric & Water Systems up to 27 °C |

Technical

| | |
|----------------------------|--|
| Max side of sound knots: | 30mm in diameter |
| Max size of broken knots: | 30mm diameter |
| Sapwood: | Acceptable up to 30% of the board |
| Filler & colour variation: | Allowed |
| Small cracks: | Acceptable up to 2mm wide & 100mm long |
| Inner bark: | Allowed |
| Origin of timber: | Europe |
| Layers of lacquer/oil | 6 |

Warranty

| | |
|--------------|-----|
| Residential: | N/A |
| Commercial: | N/A |

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.