



# GALLERIA

CLASSIC

UK FLOORING DIRECT



## Product Data Sheet

**ENG-GA-18-508**

Scan the QR code for fast access to this floor online

## Galleria Classic Engineered European Rustic Oak Flooring 18mm x 150mm Natural Brushed & Oiled

If it's a traditional wood-floor look you're after, then Galleria Classic Engineered European Rustic Oak deserves your attention. Random-length planks and lively grain markings give this quality European oak floor a relaxed feel that will make any room feel instantly more homely.

The attractive swirling patterns, multiple knots and colour variation that is characteristic of rustic-grade oak are lifted by the brushed finish, while a premium UV oil coating gives this beautiful floor a truly natural look that will suit a wide range of interior styles. To maintain your floor, simply vacuum and damp-mop occasionally. The classic-width (150mm), long-length planks – in varying lengths up to 1800mm – give excellent coverage and work best in longer rooms, where they will help the floor appear in proportion to the space and give a classic, well-fitted look.

Offering exceptional stability, the floor features a high-quality multi-layer construction of several layers of plywood topped with a 4mm hardwood wear layer for a dense feel underfoot and optimum grain definition. With a traditional tongue-and-groove fixing, this load-bearing floor requires professional installation for best results.

### Product Details

<b>Code:</b>	ENG-GA-18-508
<b>Brand:</b>	Galleria Classic
<b>Construction:</b>	Engineered Multi-Ply
<b>Species:</b>	Oak
<b>Grade:</b>	Rustic
<b>Design:</b>	Plank
<b>Surface:</b>	Brushed
<b>Finish:</b>	UV Oiled
<b>Profile:</b>	Tongue & Groove
<b>Edge profile:</b>	Bevelled on 4 sides
<b>Top layer:</b>	4mm
<b>Core:</b>	Softwood
<b>Thickness:</b>	18mm
<b>Width:</b>	150mm
<b>Length:</b>	400mm - 1800mm
<b>Coverage per pack:</b>	1.35m <sup>2</sup>

### Warranty

<b>Residential:</b>	N/A
<b>Commercial:</b>	N/A

NB: Please ask for full warranty terms and conditions

### Installation

<b>Fully-bonded:</b>	Yes
<b>Nailed:</b>	Yes
<b>Floated on underlay:</b>	No
<b>Over underfloor heating:</b>	Yes, Water Systems up to 27 °C

### Technical

<b>Max side of sound knots:</b>	50mm diameter
<b>Max size of broken knots:</b>	40mm diameter
<b>Sapwood:</b>	Acceptable up to 10% of the board
<b>Filler &amp; colour variation:</b>	Allowed
<b>Small cracks:</b>	Acceptable up to 3mm wide & 300mm long
<b>Inner bark:</b>	Allowed
<b>Origin of timber:</b>	Europe
<b>Responsible certification:</b>	N/A
<b>Janka hardness rating:</b>	1360

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.