



GALLERIA

CLASSIC

Product Data Sheet

ENG-GA-18-509

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Galleria Classic Engineered Rustic Oak Flooring 18mm x 150mm Metal Grey Brushed & Lacquered

If you're looking to install a stunning real wood floor, then look no further than our Galleria Classic Engineered Rustic Oak Metal Grey flooring. With random-length planks and defined, natural looking lines, this floor will provide a fantastic rustic look to your home. With a stunning pewter-grey colouring, this floor combines the traditional look of real wood with the contemporary style of grey flooring for the perfect mix of old and new. These boards have been brushed to help bring out the natural pattern within the real wood surface, they are then finished with UV lacquer to provide increased durability and ensure your new floor looks brilliant for longer.

The classic-width (150mm), random-length planks – in varying lengths of up to 1800mm – give excellent coverage and work best in longer rooms, where they will help the floor appear in proportion to the space and give a classic, well-fitted look.

Offering exceptional stability, the floor features a high-quality multi-layer construction of several layers of plywood topped with a 4mm hardwood wear layer for a dense feel underfoot and optimum grain definition. With a traditional tongue-and-groove fixing, this load-bearing floor requires professional installation for best results.

Product Details

Code:	ENG-GA-18-509
Brand:	Galleria Classic
Construction:	Engineered Multi-Ply
Species:	Oak
Design:	Plank
Surface:	Brushed
Finish:	Brushed & UV Lacquer
Profile:	Tongue & Groove
Edge profile:	Bevelled on 4 sides
Top layer:	4mm
Core:	N/A
Thickness:	18mm
Width:	150mm
Length:	400mm–1800mm
Grade:	Rustic
Coverage per pack:	1.35m ²

Warranty

Residential:	20 years
Commercial:	5 years

Installation

Fully bonded:	Yes
Floated on underlay:	Yes
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

Technical

Max side of sound knots:	Acceptable without limit
Max size of broken knots:	50mm diameter
Sapwood:	Acceptable up to 50% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 3mm wide & 200mm long
Inner bark:	Allowed
Origin of timber:	Europe
Layers of lacquer/oil	6

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.