



GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



Product Data Sheet

ENG-GAL-002

Scan the QR code for fast access to this floor online

Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Brushed & Oiled

A premium engineered wood floor that is as hardwearing as it is beautiful, Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Brushed & Oiled is an investment for life. Blessed with warm oak tones and a relaxed, natural appearance, this truly timeless floor will add a welcoming feel to any room in the home.

Made using finest European oak in a rustic grade – characterised by lively grain markings, knots of all sizes, sapwood and small mineral streaks – it has an attractive brushed finish and has been treated with protective high-quality UV oil for an enhanced lifespan. Vacuuming and occasional cleaning with a damp mop is all it takes to keep this floor looking its best. The wide, long-length planks (190mm x 1900mm) are ideally suited to spacious interiors, particularly longer rooms where they will help to make the floor look in proportion and create a feeling of elegance.

Offering exceptional stability, this load-bearing tongue-and-groove floor is 20mm thick and features a multi-layer construction of several layers of plywood topped with a 6mm hardwood wear layer for a dense feel underfoot and optimum grain definition. For best results, professional installation is recommended.

Product Details

Code:	ENG-GAL-002
Brand:	Galleria Professional
Construction:	Engineered Multi-Ply
Species:	Oak
Grade:	Rustic
Design:	Plank
Surface:	Brushed
Finish:	UV Oiled
Profile:	Tongue & Groove
Edge profile:	Bevelled on 4 sides
Top layer:	6mm
Core:	Softwood
Thickness:	20mm
Width:	190mm
Length:	1900mm
Coverage per pack:	1.81m ²

Warranty

Residential:	N/A
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Fully-bonded:	Yes
Nailed:	Yes
Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Max side of sound knots:	50mm diameter
Max size of broken knots:	40mm diameter
Sapwood:	Acceptable up to 30% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 5mm wide & 300mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.