



UK **FLOORING** DIRECT

Product Data Sheet

ENG-GAL-102

Galleria Professional Engineered European Rustic Oak Flooring 20mm X 190mm Ground Coffee Lacquered

A truly stunning floor with warm brown tones that highlights natural oak in all its glory, Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Ground Coffee Lacquered is the perfect choice for homeowners seeking a traditional wood floor that is both striking and easy to care for.

A brushed finish allows all the rich grain markings, knots and colour variations of this rustic-grade, high-quality European oak to be clearly seen, giving the floor a timeless look that will tone beautifully with a wide range of interior schemes. The floor is finished with a durable UV lacquer for hardwearing protection and ease of maintenance; regular vacuuming and damp mopping is all it takes to keep this floor looking its best.

The fixed-length wide, long planks (190mm x 1900mm) are an ideal size for creating a feeling of elegance in spacious rooms, and can help longer rooms appear more in proportion. Promising a lifetime of good looks, Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Ground Coffee Lacquered features a multi-layer construction for enhanced stability while a premium 6mm wood wear layer that gives true depth and definition to the grain. For best results, we recommend this load-bearing tongue-and-groove floor is fitted by a professional.

Product Details

Code	ENG-GAL-102
Brand	Galleria Professional
Construction	Engineered Multi-Ply
Species	Oak
Grade	Rustic
Design	Plank
Surface	Brushed
Finish	UV Lacquer
Profile	Tongue & Groove
Edge profile	Bevelled on 4 sides
Top layer	6mm
Core	Softwood
Thickness	20mm
Width	190mm
Length	1900mm
M ² per pack	1.805m ²

Installation

Fully-bonded	Yes
Nailed	Yes
Floated on underlay	Yes
Over underfloor heating	Yes, Water Systems up to 27 °C

Technical

Max size of sound knots	50mm Diameter
Max size of broken knots	40mm Diameter
Sapwood	Acceptable up to 30% of the board
Filler & colour variation	Allowed
Small cracks	Acceptable up to 3mm wide & 150mm long
Inner bark	Allowed
Origin of timber	Europe
Responsible certification	N/A
Janka hardness rating	1360

Warranty

Residential	N/A
Commercial	N/A

NB: Please ask for full warranty terms and conditions

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ

Tel: 02476 012840 | Fax: 02476 397828

info@ukflooringdirect.co.uk

ukflooringdirect.co.uk

© This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.

*Subject to compatible subfloor & correct installation ** Call for more information.