



GALLERIA

PROFESSIONAL

UK FLOORING DIRECT



Product Data Sheet

ENG-GAL-102

Scan the QR code for fast access to this floor online

Galleria Professional Engineered European Rustic Oak Flooring 20mm X 190mm Ground Coffee Lacquered

A truly stunning floor with warm brown tones that highlights natural oak in all its glory, Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Ground Coffee Lacquered is the perfect choice for homeowners seeking a traditional wood floor that is both striking and easy to care for.

A brushed finish allows all the rich grain markings, knots and colour variations of this rustic-grade, high-quality European oak to be clearly seen, giving the floor a timeless look that will tone beautifully with a wide range of interior schemes. The floor is finished with a durable UV lacquer for hardwearing protection and ease of maintenance; regular vacuuming and damp mopping is all it takes to keep this floor looking its best. The fixed-length wide, long planks (190mm x 1900mm) are an ideal size for creating a feeling of elegance in spacious rooms, and can help longer rooms appear more in proportion.

Promising a lifetime of good looks, Galleria Professional Engineered European Rustic Oak Flooring 20mm x 190mm Ground Coffee Lacquered features a multi-layer construction for enhanced stability while a premium 6mm wood wear layer that gives true depth and definition to the grain. For best results, we recommend this load-bearing tongue-and-groove floor is fitted by a professional.

Product Details

Code:	ENG-GAL-102
Brand:	Galleria Professional
Construction:	Engineered Multi-Ply
Species:	Oak
Grade:	Rustic
Design:	Plank
Surface:	Brushed
Finish:	UV Lacquer
Profile:	Tongue & Groove
Edge profile:	Bevelled on 4 sides
Top layer:	6mm
Core:	Softwood
Thickness:	20mm
Width:	190mm
Length:	1900mm
Coverage per pack:	1.81m ²

Warranty

Residential:	N/A
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Fully-bonded:	Yes
Nailed:	Yes
Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Max side of sound knots:	50mm diameter
Max size of broken knots:	40mm diameter
Sapwood:	Acceptable up to 30% of the board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 5mm wide & 300mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.