



# HOME CHOICE

floors made for living

UK FLOORING DIRECT



## Product Data Sheet

**ENG-HC-14-302**

Scan the QR code for fast access to this floor online

## Home Choice Engineered European Rustic Oak Flooring 14mm x 190mm Blonde Matt Lacquered

With its lively grain markings and beautiful pale oak tones, this Home Choice engineered wood floor will create a lived-in, laidback look in a broad range of spaces. Made using quality European oak in a rustic grade that celebrates its natural characteristics, this striking floor features visible knots and colour variation for maximum visual interest, while a brushed finish allows the wood to retain a more textured look and feel that enhances its modern charm.

Home Choice Engineered European Rustic Oak Flooring 14mm x 190mm Blonde Matt Lacquered is also incredibly easy to care for, offering great durability and stain resistance thanks to its matt lacquer coating. The random-length planks (400mm x 1900mm) will beautifully enhance any room giving a classic wood-floor look. Lastly, with its 5G click system this floor is ideal for even easier and faster DIY installation.

### Product Details

<b>Code:</b>	ENG-HC-14-302
<b>Brand:</b>	Home Choice
<b>Construction:</b>	Engineered 3-Ply
<b>Species:</b>	Oak
<b>Grade:</b>	Rustic
<b>Design:</b>	Plank
<b>Surface:</b>	Matt Lacquered
<b>Finish:</b>	Brushed
<b>Profile:</b>	5G Click System
<b>Edge profile:</b>	Micro Bevel 4 Sides
<b>Top layer:</b>	3mm
<b>Core:</b>	European Oak
<b>Thickness:</b>	14mm
<b>Width:</b>	190mm
<b>Length:</b>	400mm - 1900mm
<b>Coverage per pack:</b>	2.888m <sup>2</sup>

### Warranty

<b>Residential:</b>	20 years
<b>Commercial:</b>	5 years

NB: Please ask for full warranty terms and conditions

### Installation

<b>Fully-bonded:</b>	Yes
<b>Nailed:</b>	Yes
<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes, Electric & Water Systems up to 27 °C

### Technical

<b>Max side of sound knots:</b>	Acceptable without limit
<b>Max size of broken knots:</b>	50mm in diameter
<b>Sapwood:</b>	Acceptable up to 50% of the board
<b>Filler &amp; colour variation:</b>	Allowed
<b>Small cracks:</b>	Acceptable up to 2mm wide & 200mm long
<b>Inner bark:</b>	Allowed
<b>Origin of timber:</b>	Europe
<b>Responsible certification:</b>	EUTR
<b>Janka hardness rating:</b>	1360

### UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG  
Tel: 02476 012 840  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2023. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.