



HOME CHOICE

floors made for living

UK FLOORING DIRECT



Product Data Sheet

ENG-HCB-14-001

Scan the QR code for fast access to this floor online

Home Choice Herringbone Engineered European Select Oak Flooring 14mm x 130mm Caramel Lacquered

If you love the timeless and chic look of herringbone, this stylish floor is for you. Home Choice Herringbone Engineered European Select Oak Flooring 14mm x 130mm Caramel Lacquered boasts a gorgeous golden tone that celebrates natural oak at its beautiful best, and features a simple click system that allows for fast installation, bringing this fabulous flooring style within easy reach of every homeowner.

Made from finest European oak in a select grade, it features occasional small knots and limited marks and streaks for a clean, understated look. A great fit for any size of room, the 725mm long micro-bevelled planks have been gently brushed to enhance their texture and finished with a low-sheen matt UV lacquer that offers excellent durability and resistance to stains and marks.

Delivering a classic, ageless look wherever it's laid, this beautiful floor has a three-layer construction for great stability and a standard 2.5mm real wood wear layer for an enhanced lifespan. Vacuuming and occasional light mopping should ensure it looks fantastic for years to come.

Product Details

Code:	ENG-HCB-14-001
Brand:	Home Choice
Construction:	Engineered 3-Ply
Species:	Oak
Grade:	Select
Design:	Plank
Surface:	Brushed
Finish:	UV Matt Lacquered
Profile:	Click System
Edge profile:	Micro Bevelled on 4 sides
Top layer:	2.5mm
Core:	Softwood
Thickness:	14mm
Width:	130mm
Length:	725mm
Coverage per pack:	0.65m ²

Warranty

Residential:	20 years
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Fully-bonded:	Yes
Nailed:	No
Floated on underlay:	No
Over underfloor heating:	Yes, Electric & Water Systems up to 27 °C

Technical

Max side of sound knots:	35mm in diameter
Max size of broken knots:	25mm in diameter
Sapwood:	Acceptable up to 10% from edge of board
Filler & colour variation:	Allowed
Small cracks:	Acceptable up to 5mm wide & 200mm long
Inner bark:	Allowed
Origin of timber:	Europe
Responsible certification:	N/A
Janka hardness rating:	1360

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustrative purposes only.