



# HOME CHOICE

floors made for living

UK FLOORING DIRECT



## Product Data Sheet

**ENG-HCB-14-308**

Scan the QR code for fast access to this floor online

## Home Choice Engineered European Rustic Oak Herringbone Flooring 14mm x 150mm Natural Matt Lacquered

If you love the timeless and chic look of herringbone, this stylish floor is for you. Home Choice Herringbone Engineered European Rustic Oak Flooring 14mm x 150mm Natural Matt Lacquered is a classic herringbone look with its characterful grain giving your floor an inviting rustic vibe.

This rustic grade floor features multiple knots, sapwood, mineral streaks, and colour variation for maximum visual interest. The boards have been sanded smooth for a modern look on a classic colour. The 600mm classic micro-bevelled planks will work in any size of room and are protected with a matt lacquer that offers excellent durability and resistance to stains and marks.

This floor features a click-together system for fast and easy DIY installation. A real all-rounder that's both beautiful and easy to care for; simply vacuum and damp mop to keep your floor looking its best.

### Product Details

<b>Code:</b>	ENG-HCB-14-308
<b>Brand:</b>	Home Choice
<b>Construction:</b>	Engineered Multi-Ply
<b>Species:</b>	Oak
<b>Grade:</b>	Rustic
<b>Design:</b>	Herringbone
<b>Surface:</b>	Matt Lacquered
<b>Finish:</b>	Smooth
<b>Profile:</b>	Click System
<b>Edge profile:</b>	Micro Bevel 4 Sides
<b>Wear Layer/Top Layer:</b>	3mm
<b>Core:</b>	European Oak
<b>Thickness:</b>	14mm
<b>Width:</b>	150mm
<b>Length:</b>	600mm
<b>Coverage per pack:</b>	1.44m <sup>2</sup>

### Warranty

<b>Residential:</b>	20 years
<b>Commercial:</b>	5 years

NB: Please ask for full warranty terms and conditions

### Installation

<b>Fully-bonded:</b>	Yes
<b>Nailed:</b>	Yes
<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes, Electric & Water Systems up to 27 °C

### Technical

<b>Max side of sound knots:</b>	Acceptable without limit
<b>Max size of broken knots:</b>	50mm in diameter
<b>Sapwood:</b>	Acceptable up to 50% of the board
<b>Filler &amp; colour variation:</b>	Allowed
<b>Small cracks:</b>	Acceptable up to 2mm wide & 200mm long
<b>Inner bark:</b>	Allowed
<b>Origin of timber:</b>	Europe
<b>Responsible certification:</b>	EUTR
<b>Janka hardness rating:</b>	1360

### UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG  
Tel: 02476 012 840  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2023. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.