



HOME CHOICE

floors made for living

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Product Data Sheet

ENG-HCB-14-313

Home Choice Engineered European Rustic Oak Herringbone Flooring 14mm x 150mm Platinum Matt Lacquered

Made from premium European oak, this striking wood floor features on-trend concrete tones that lend it a strong architectural feel and distinctly contemporary edge. Home Choice Engineered European Rustic Oak Herringbone Flooring 14mm x 150mm Platinum Matt Lacquered delivers a contemporary look in modern homes and features a DIY friendly click together system bringing this fabulous flooring style within easy reach of every homeowner.

Featuring a soft, characterful grain giving your home an inviting modern rustic look. The classic 600mm long micro-bevelled planks have been gently brushed to enhance their texture and finished with a low-sheen UV lacquer that offers excellent durability and resistance to stains and marks.

Delivering a classic herringbone look in any size of room, large or small, this beautiful floor is easy to care for. Vacuuming and occasional light mopping is all that is required to ensure it looks fantastic for years to come..

Product Details

| | |
|---------------------------|------------------------|
| Code: | ENG-HCB-14-313 |
| Brand: | Home Choice |
| Construction: | Engineered Multi-Ply |
| Species: | Oak |
| Grade: | Rustic |
| Design: | Herringbone |
| Surface: | Matt Lacquered |
| Finish: | Brushed |
| Profile: | Click System |
| Edge profile: | Micro Bevel on 4 sides |
| Top layer: | 3mm |
| Core: | European Oak |
| Thickness: | 14mm |
| Width: | 150mm |
| Length: | 600mm |
| Coverage per pack: | 1.44m ² |

Warranty

| | |
|---------------------|----------|
| Residential: | 20 years |
| Commercial: | 5 years |

NB: Please ask for full warranty terms and conditions

Installation

| | |
|---------------------------------|---|
| Fully-bonded: | Yes |
| Nailed: | Yes |
| Floated on underlay: | Yes |
| Over underfloor heating: | Yes, Electric & Water Systems up to 27 °C |

Technical

| | |
|---------------------------------------|--|
| Max side of sound knots: | Acceptable without limit |
| Max size of broken knots: | 50mm in diameter |
| Sapwood: | Acceptable up to 50% of the board |
| Filler & colour variation: | Allowed |
| Small cracks: | Acceptable up to 2mm wide & 200mm long |
| Inner bark: | Allowed |
| Origin of timber: | Europe |
| Responsible certification: | EUTR |
| Janka hardness rating: | 1360 |

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG
Tel: 02476 012 840

info@ukflooringdirect.co.uk

ukflooringdirect.co.uk

© 2023. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.