



AQUALOCK

WATER RESISTANT FLOORS

Product Data Sheet

LAM-AL-10-001

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Aqualock Aqualock 10mm Laminate Flooring Wade Oak

The striking grey of Aqualock 10mm Laminate Flooring Wade Oak is sure to brew up a storm in your home. The perfect of-the-moment tones of this wood-effect floor add a sense of sophistication to the premium look and feel of its embossed surface markings, creating a floor with contemporary appeal that will still complement a classic interior scheme. Full of benefits thanks to its modern laminate construction, such as added protection against moisture and spills from its 72-hour water-resistance and UV resistance to help prevent fading.

Enjoy peace of mind with Aqualock 10mm Laminate Flooring Wade Oak thanks to its AC5 Commercial rating as well as 5-year commercial and 25-year residential warranty. Perfectly proportioned to fit in any room with 1285mm x 158mm bevel edged boards, this floor is also fast and easy to install thanks to its DIY-friendly click system — perfect even for novice fitters. Easy to maintain and simple to care for, Aqualock Laminate Flooring just needs vacuuming regularly and cleaning occasionally with a damp mop.

Product Details

Code:	LAM-AL-10-001
Brand:	Aqualock
Construction:	Laminate
Surface:	EIR
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	10mm
Width:	158mm
Length:	1285mm
Coverage per pack:	1.624m ²
AC rating:	AC5 Commercial

Warranty

Residential:	25 Years
Commercial:	5 Years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	Water Resistant (Up to 24 Hours)
Technical Class:	33
Fire resistance:	EN 13501-1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN ISO 4892-2
VOC emissions:	A+
Thickness swelling:	EN 13329
Environmental certification:	PEFC
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.