



AQUALOCK

WATER RESISTANT FLOORS

Product Data Sheet

LAM-AL-8-003

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Aqualock Aqualock 8mm Laminate Flooring Waterfall Oak

With a delightful and on-trend grey tone, Aqualock 8mm Laminate Flooring Waterfall Oak offers a twist on a contemporary favourite thanks to its relaxed vibes. A classic board that makes for a great choice throughout the home, with a relaxed and authentic grain matching perfectly to a modern hue that pairs with a range of interior styles. With 72-hour water-resistance giving added protection against moisture and spills, as well as UV resistance to stop it from fading and losing its looks over time, this floor makes the most of modern laminate construction.

Thanks to its classically proportioned bevel edged boards measuring in at 1285mm x 192mm, Aqualock 8mm Laminate Flooring Waterfall Oak is ideal for helping small and medium sized rooms to feel more spacious but still works brilliantly in almost any space. With its AC4 Heavy Domestic rating and 20-year residential warranty, you will get plenty of peace of mind with this floor. A great low maintenance floor that's easy to care for, just needing vacuuming regularly and cleaning occasionally with a damp mop, and fast and easy to install thanks to its DIY-friendly click system.

Product Details

Code:	LAM-AL-8-003
Brand:	Aqualock
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	8mm
Width:	192mm
Length:	1285mm
Coverage per pack:	1.973m ²
AC rating:	AC4 Heavy Domestic

Warranty

Residential:	20 Years
Commercial:	N/A

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	Water Resistant (Up to 24 Hours)
Technical Class:	32
Fire resistance:	EN 13501-1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN ISO 4892-2
VOC emissions:	A+
Thickness swelling:	EN 13329
Environmental certification:	PEFC
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.