



**AQUALOCK**  
WATER RESISTANT FLOORS

## Product Data Sheet

**LAM-AL-8-320**

UK **FLOORING** DIRECT



Scan the QR code for fast access to this floor online

## Aqualock 8mm Laminate Flooring Farmhouse Oak

Boasting a gorgeous natural oak tone and subdued grain guaranteed to bring a relaxed, welcoming look to any room, Aqualock 8mm Laminate Flooring Farmhouse Oak offers all the beauty of a traditional-style wood-look floor with the practical benefits of a modern laminate construction.

With added protection against moisture and spills, it's ready to take on the toughest of tasks. Made in Europe harnessing the latest technology, Aqualock Laminate remains water resistant for up to 24 hours and features a tough, scratch-resistant textured surface for an authentic feel. With UV resistance that prevents fading, this floor is great for use throughout the home. Aqualock 8mm Laminate Flooring Farmhouse Oak comes in bevel-edged classic-size boards (191mm x 1380mm) that are ideal for making small and medium-length rooms appear larger.

The floor is fast and easy to fit thanks to a DIY-friendly click system. With an AC5 Commercial rating and a 35-year warranty for complete peace of mind, Aqualock Laminate Flooring is also simple to care for. Just vacuum regularly and clean occasionally with a damp mop.

### Product Details

<b>Code:</b>	LAM-AL-8-320
<b>Brand:</b>	Aqualock
<b>Construction:</b>	Laminate
<b>Surface:</b>	Authentic Textured
<b>Profile:</b>	Click System
<b>Edge profile:</b>	Bevelled on 4 sides
<b>Thickness:</b>	8mm
<b>Width:</b>	191mm
<b>Length:</b>	1380mm
<b>Coverage per pack:</b>	2.13m <sup>2</sup>
<b>AC rating:</b>	AC5 - Commercial

### Warranty

<b>Residential:</b>	35 Years
<b>Commercial:</b>	N/A

NB: Please ask for full warranty terms and conditions

### Installation

<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes, Water Systems

### Technical

<b>Water rating:</b>	Water Resistant
<b>Technical Class:</b>	Class 33
<b>Fire resistance:</b>	EN 13501-1
<b>Formaldehyde emission:</b>	EN 717-1
<b>Slip resistance:</b>	DS
<b>Thermal resistance/conductivity:</b>	EN 12667
<b>Resistance to staining:</b>	EN 438
<b>Wear resistance:</b>	EN 13329
<b>Effects of furniture leg:</b>	EN 424
<b>Effects of castor chair:</b>	EN 425
<b>Light fastness:</b>	EN 13329
<b>VOC emissions:</b>	ISO 16000
<b>Thickness swelling:</b>	EN 13329
<b>Tolerance:</b>	EN 13329

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.