



AQUALOCK
WATER RESISTANT FLOORS

Product Data Sheet

LAM-AL-8-324

UK **FLOORING** DIRECT



Scan the QR code for fast access to this floor online

Aqualock 8mm Laminate Flooring Beach House Oak

Through cool sandy tones and an attractive swirling grain, perfect for creating a laidback, relaxed vibe, Aqualock 8mm Laminate Flooring Beach House Oak offers all the beauty of a vintage wood-look with the practical benefits of a modern laminate construction. With added protection against moisture and spills, it's ready to take on the toughest of tasks.

Made in Europe harnessing the latest technology, Aqualock Laminate remains water resistant for up to 24 hours and features a tough, scratch-resistant textured surface for an authentic feel. With UV resistance that prevents fading, this floor is great for use throughout the home. Aqualock 8mm Laminate Flooring Beach House Oak comes in bevel-edged classic-size boards (191mm x 1380mm) that are ideal for making small and medium-length rooms appear larger.

The floor is fast and easy to fit thanks to a DIY-friendly click system. With an AC5 Commercial rating and a 35-year warranty for complete peace of mind, Aqualock Laminate Flooring is also simple to care for. Just vacuum regularly and clean occasionally with a damp mop.

Product Details

Code:	LAM-AL-8-324
Brand:	Aqualock
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	8mm
Width:	191mm
Length:	1380mm
Coverage per pack:	2.13m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	35 Years
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	Water Resistant
Technical Class:	Class 33
Fire resistance:	EN 13501-1
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.