



Product Data Sheet

LAM-AU-12-307

Scan the QR code for fast access to this floor online

Audacity 12mm Laminate Flooring Meadow Oak

Evoking the organic beauty of a traditional oak floor, Audacity 12mm Laminate Flooring Meadow Oak is practical as well as stunning. This fearless water-resistant laminate will stand up to every challenge family life can throw at it. Spill, splash and pet-proof, it comes with a lifetime residential guarantee and can be safely used in bathrooms and kitchens.

With varied grain markings, a hand-scraped texture and bevelled boards for an incredibly authentic wood look, Audacity 12mm Laminate Flooring Meadow Oak features wide, classic-length planks that will help to make small and medium-length rooms appear longer and are quick and easy to fit thanks to a DIY-friendly Tight Lock click system. With a built-in backing pad that helps to reduce sound, Audacity floors can be installed without underlay.

What's more, Audacity's 35% more stable core means less chance of movement and better stability across the biggest spaces. An AC4 Heavy Domestic wear rating makes Audacity the perfect 'go anywhere' floor and it is recommended for demanding areas such as bathrooms, kitchens and conservatories. With a tough stain and scuff-resistant surface, spills, dirt and accidents can simply be wiped away, leaving your Audacity floor looking as good as new.

Product Details

Code:	LAM-AU-12-307
Brand:	Audacity
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	12mm
Width:	196mm
Length:	1213mm
Coverage per pack:	1.43m ²
AC rating:	AC4 - Heavy Domestic

Warranty

Residential:	Lifetime
Commercial:	5 Years

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Underlay built in to boards
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	Water Resistant
Technical Class:	Class 32
Fire resistance:	EN 13501-1
Formaldehyde emission:	ASTM D6007
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	EN 433
Effects of castor chair:	EN 433
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.