



SERIES

FLOORING

UK **FLOORING** DIRECT



Scan the QR code for fast access to this floor online

Product Data Sheet

LAM-MD-10-395

Series Woods 10mm Laminate Flooring Wild Dove Oak

In classic dove grey hues that are incredibly versatile, Series Woods 10mm Laminate Flooring Wild Dove Oak brings a timeless elegance in any interior. This floor is the perfect way to add grounding to a neutral scheme or bring balance to adventurous colours.

An authentic textured surface reflects the natural detail of oak for a more realistic wood effect, while Wild Dove Oak's v-groove between each plank adds definition for a classic wood floor look. The wide, regular length plank (193 x 1380mm) is suited to a good range of room sizes, working to make rooms feel more spacious.

Ready for quick and easy DIY fitting thanks to its click together planks, Series Woods 10mm Laminate Flooring Wild Dove Oak has a tough and hardwearing finish that's simple to look after. With an AC4 rating that makes it suitable for use throughout busy family homes, though not in bathrooms, this great value style is ideal for anyone looking for a floor that's easy to enjoy.

Series Woods 10mm Laminate Flooring Wild Dove Oak comes with a 25-year warranty and is suitable for use with water underfloor heating.

Product Details

Code:	LAM-MD-10-395
Brand:	Series Woods
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	10mm
Width:	193mm
Length:	1380mm
Coverage per pack:	1.59m ²
AC rating:	AC4 - Heavy Domestic

Warranty

Residential:	25 Years
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	N/A
Technical Class:	Class 32
Fire resistance:	EN 13501
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

UK Flooring Direct

Unit H4 Pilgrims Walk, Prologis Park, Coventry, CV6 4QG
Tel: 02476 012 840
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2023. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.