



# SERIES

## FLOORING<sup>PRO</sup>

UK FLOORING DIRECT



### Product Data Sheet

**LAM-SE-10-019**

Scan the QR code for fast access to this floor online

## Series Woods Professional 10mm Laminate Flooring Grey Oak

With stormy undertones and a swirling oak grain captured in deepest charcoal, Series Woods Professional 10mm Laminate Flooring Grey Oak brings a touch of drama, for those who prefer a floor with a characterful, vintage vibe.

Manufactured in Europe, this 10mm thick, professional quality laminate features an authentic textured surface that follows the expressive grain markings beneath, adding extra realism to its super-tough matt finish. The mid-width, mid-length planks (157mm x 1380mm) are great all-rounders and are particularly well suited to creating a classic, space enhancing look in medium-length rooms, while their four-sided bevel helps to bring variety to the floor through edge defining detail.

A breeze to look after (requiring only vacuuming and damp mopping) and with a 30-year warranty promising long-lasting good looks, this AC5 Commercial rated professional floor makes sense for the busiest of homes, where its durability will deliver in high-traffic areas such as kitchens, hallways and living spaces. Fast and easy to fit thanks to its 5G click together joint, Series Woods Professional Grey Oak offers both fantastic quality and bags of style, making it a fabulous all-round flooring choice.

### Product Details

Code:	LAM-SE-10-019
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	Authentic Textured
Profile:	5G Click System
Edge profile:	Bevelled on 4 sides
Thickness:	10mm
Width:	157mm
Length:	1380mm
Coverage per pack:	1.30m <sup>2</sup>
AC rating:	AC5 - Commercial

### Warranty

Residential:	30 Years
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

### Technical

Water rating:	N/A
Technical Class:	Class 33
Fire resistance:	EN 13501
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.