



SERIES

FLOORING^{PRO}

UK FLOORING DIRECT



Product Data Sheet

LAM-SE-12-019

Scan the QR code for fast access to this floor online

Series Woods Professional 12mm Laminate Flooring Lion Oak

With its soft, hued-out caramel tones and lively grain patterns, Series Woods Professional 12mm Laminate Flooring Lion Oak combines the stunning looks of a traditional-style wood floor with all the practical advantages of a high-quality, hardwearing laminate.

Series Woods Professional 12mm Laminate Flooring is produced in Europe using the latest technology and features a textured surface and realistic markings such as saw cuts and small knots to replicate the charm – and solid feel – of real wood. Maintenance is simple; just regular vacuuming and mopping with water is all that is required to leave this floor looking its best. The 193mm wide boards feature come in a classic length (1380mm) that is ideal for making small and medium-length rooms appear larger, while a 5G click fitting system, with joints on all four sides of each board, makes DIY installation fast and easy.

At 12mm thick, this great-value floor comes with an AC5 Commercial Grade rating and an impressive 35-year warranty, and is suitable for all rooms in the home including areas of heavy traffic.

Product Details

Code:	LAM-SE-12-019
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	Authentic Textured
Profile:	5G Click System
Edge profile:	Bevelled on 4 sides
Thickness:	12mm
Width:	193mm
Length:	1380mm
Coverage per pack:	1.33m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	35 Years
Commercial:	N/A

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

Technical

Water rating:	N/A
Technical Class:	Class 33
Fire resistance:	EN 13501-1
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.