



# SERIES

## FLOORING<sup>PRO</sup>

UK FLOORING DIRECT



### Product Data Sheet

**LAM-SE-12-356**

Scan the QR code for fast access to this floor online

## Series Woods Professional 12mm Laminate Flooring Bisque Oak

With the look and feel of wood behind it, Series Woods Professional 12mm Laminate Flooring Bisque Oak is ready for the trials of a busy home and has brought plenty of style with it. The muted hue offers a contemporary look that lends itself perfectly to setting a minimalist mood in your home. With its clean and elegant grain pattern resting beneath an embossed in register texture, the four bevelled edges of each plank give the finished floor depth and definition.

The perfect all-rounder with 12mm thick planks that measure in at 157mm wide and 1285mm long, this floor is ideally suited for creating a space-enhancing look especially in medium-length rooms. With its DIY-friendly click-together joint system, this floor is a great choice for those looking for a fast and easy fitting they can perform themselves.

Offering the level of unbeatable performance to match its style sought after by every busy home, Series Woods Professional 12mm Laminate Flooring Bisque Oak comes with an AC5 Commercial rating and a 30-year warranty for your complete peace of mind. And it's easy to keep this floor looking its best, needing only regular vacuuming and a damp mop from time to time.

### Product Details

Code:	LAM-SE-12-356
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	EIR
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	12mm
Width:	157mm
Length:	1285mm
Coverage per pack:	1.21m <sup>2</sup>
AC rating:	AC5 Commercial

### Warranty

Residential:	30 Years
Commercial:	5 Years

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, up to a max of 27°C

### Technical

Water rating:	Splash-proof
Technical Class:	23/32
Fire resistance:	Class CfL – S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	R23 / $\leq 0.1$ (m_K)/W
Resistance to staining:	EN 13329
Wear resistance:	EN 13329
Effects of furniture leg:	EN 13329
Effects of castor chair:	EN 13329
Light fastness:	EN 20105-B02
VOC emissions:	A+
Thickness swelling:	EN 13329
Environmental certification:	FSC
Tolerance:	EN 13329

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.