



SERIES FLOORING

UK FLOORING DIRECT



Product Data Sheet

LAM-SE-8-031

Scan the QR code for fast access to this floor online

Series Woods 8mm Laminate Flooring Koala Grey

For a floor with modern appeal that offers a tone which can truly go with just about anything, Koala Grey Laminate fits the bill. Its soft shade of grey and subtle grain not only pair well with most interior styles, but its lighter tone is ideal for brightening up your room, bringing a sophisticated and modern look. To add to this contemporary appeal, each board has a square edge profile that gives the finished floor a smooth look. Thanks to its click fitting system, Series Woods 8mm Laminate Flooring Koala Grey is incredibly DIY friendly, meaning even amateur DIYers can bring this look into their home.

This floor is set to make an impression in your home with the classic dimensions of the planks (1200mm x 193mm) that will help a room to feel not only brighter but bigger as well. With its AC3 wear rating, this floor can offer great style and reliability throughout your house, especially in living rooms and bedrooms, though it is not suitable for bathrooms.

Product Details

| | |
|--------------------|--------------------|
| Code: | LAM-SE-8-031 |
| Brand: | Series Woods |
| Construction: | Laminate |
| Surface: | Authentic Textured |
| Profile: | Click System |
| Edge profile: | Square Edge |
| Thickness: | 8mm |
| Width: | 193mm |
| Length: | 1200mm |
| Coverage per pack: | 1.85m ² |
| AC rating: | AC3 - Domestic |

Warranty

| | |
|--------------|----------|
| Residential: | 10 years |
| Commercial: | 5 years |

Installation

| | |
|--------------------------|----------------------------------|
| Floated on underlay: | Yes |
| Over underfloor heating: | Yes, up to a max of 27°C degrees |

Technical

| | |
|----------------------------------|-------------|
| Water rating: | N/A |
| Technical Class: | 31 |
| Fire resistance: | Bfl-s1 |
| Formaldehyde emission: | E1 |
| Slip resistance: | DS |
| Thermal resistance/conductivity: | 0,1559 W/mK |
| Resistance to staining: | EN 438 - 2 |
| Wear resistance: | EN 13329 |
| Effects of furniture leg: | EN 425 |
| Effects of castor chair: | EN 424 |
| Light fastness: | EN 20105 |
| VOC emissions: | EN 120 |
| Thickness swelling: | EN 13329 |
| Tolerance: | EN 13329 |

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.