



Scan the QR code for fast access to this floor online



## Product Data Sheet

**LAM-SE-8-362**

### Series Wood Professional 8mm Herringbone Laminate Flooring Velvet Truffle Oak

The gorgeously rich tones of Herringbone Laminate Flooring Velvet Truffle Oak will add warmth and character throughout your room. Compatible with water under floor heating systems, the timeless choice of Herringbone is both a practical and stylish choice.

Featuring an authentic textured surface that enhances the oak effect, this European-made floor combines the gorgeous look and feel of wood with the practicality of laminate. With a tough top layer, it's ideal for a busy household. Boasting an AC4 rating, it's suitable for most rooms in the home, and for various commercial settings, such as small offices and hotel rooms, and requires only regular vacuuming and occasional damp mopping to stay looking its best.

In a 133mm board, the classic Herringbone pattern looks optimum in larger rooms as the full effect of the pattern can be utilised. Its four-sided bevel helps to define each plank. At 8mm thick, Herringbone Laminate Velvet Flooring Truffle Oak is suitable for heavy domestic use. Complete with a click system which makes installation a quick and easy process - the perfect option for keen DIYers. Looked after with care, this premium laminate floor is ready for lasting use.

#### Product Details

<b>Code:</b>	LAM-SE-8-362
<b>Brand:</b>	Series Woods Professional
<b>Construction:</b>	Laminate
<b>Surface:</b>	Authentic Textured
<b>Profile:</b>	Click System
<b>Edge profile:</b>	Bevelled on 4 sides
<b>Thickness:</b>	8mm
<b>Width:</b>	133mm
<b>Length:</b>	665mm
<b>Coverage per pack:</b>	1.238
<b>AC rating:</b>	AC4 - Heavy Domestic

#### Warranty

<b>Residential:</b>	25 Years
<b>Commercial:</b>	N/A

#### Installation

<b>Floated on underlay:</b>	Yes
<b>Over underfloor heating:</b>	Yes Water Systems

#### Technical

<b>Water rating:</b>	N/A
<b>Technical Class:</b>	32
<b>Fire resistance:</b>	EN 13501
<b>Formaldehyde emission:</b>	EN 717-1
<b>Slip resistance:</b>	DS
<b>Thermal resistance/conductivity:</b>	EN 12667
<b>Resistance to staining:</b>	EN 438
<b>Wear resistance:</b>	EN 13329
<b>Effects of furniture leg:</b>	EN 424
<b>Effects of castor chair:</b>	EN 425
<b>Light fastness:</b>	EN 13329
<b>VOC emissions:</b>	ISO 16000
<b>Thickness swelling:</b>	EN 13329
<b>Tolerance:</b>	EN 13329

#### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
 Tel: 02476 012840 | Fax: 02476 397828  
 info@ukflooringdirect.co.uk  
 ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.