



Scan the QR code for fast access to this floor online

Product Data Sheet

LAM-SE-8-364

Series Wood Professional 8mm Herringbone Laminate Flooring Gentle Gold Oak

The beautifully natural tones of Herringbone Laminate Flooring Gentle Gold Oak will certainly add a classic finish to your room. Perfectly imitating the natural grain of oak, this floor would work in any room of choice. Compatible with water under floor heating systems, the timeless choice of Herringbone is both a practical and stylish choice.

Featuring an authentic textured surface that enhances the oak effect, this European-made floor combines the gorgeous look and feel of wood with the practicality of laminate. With a tough top layer, it's ideal for a busy household. Boasting an AC4 heavy domestic rating, it's suitable for most rooms in the home, and for various commercial settings, such as small offices and hotel rooms, and requires only regular vacuuming and occasional damp mopping to stay looking its best.

In a 133mm board, the classic Herringbone pattern looks optimum in larger rooms as the full effect of the pattern can be utilised. Its four-sided bevel helps to define each plank. At 8mm thick, it's complete with a nifty click system which makes installation a quick and easy process as the boards simply slot together - the perfect option for those taking on a D.I.Y project. Looked after with care, this premium laminate floor is ready for lasting use.

Product Details

Code:	LAM-SE-8-364
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	8mm
Width:	133mm
Length:	665mm
Coverage per pack:	1.238
AC rating:	AC4 - Heavy Domestic

Warranty

Residential:	25 Years
Commercial:	N/A

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes Water Systems

Technical

Water rating:	N/A
Technical Class:	32
Fire resistance:	EN 13501
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
 Tel: 02476 012840 | Fax: 02476 397828
 info@ukflooringdirect.co.uk
 ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.