



Scan the QR code for fast access to this floor online



## Product Data Sheet

### LAM-SE-8-365

## Series Wood Professional 8mm Herringbone Laminate Flooring Grey Shadow Oak

Ideal for contemporary spaces, the beautifully natural tones of Herringbone Laminate Flooring Grey Shadow Oak will certainly add a characterful finish to your room. Recreate the natural finish of a real wood floor which will look incredibly stylish in any room of choice. Compatible with water under floor heating systems, the timeless choice of Herringbone is both a practical and stylish choice.

Featuring an authentic textured surface that enhances the oak effect, this European-made floor combines the gorgeous look and feel of wood with the practicality of laminate. With a tough top layer, it's ideal for a busy household. Boasting an AC4 heavy domestic rating, it's suitable for most rooms in the home, and for various commercial settings, such as small offices and hotel rooms. To keep it looking its best, regular vacuuming and occasional damp mopping is required.

In a 133mm board, the classic Herringbone pattern looks optimum in larger rooms as the full effect of the pattern can be appreciated. Its four-sided bevelled edge helps to define each plank. At 8mm thick, this floor is complete with a click system which makes installation a quick and easy process as the boards simply slot together - the perfect option for those taking on a D.I.Y project. Backed with a 25 year warranty for peace of mind, looked after with care, this hard-wearing, premium laminate floor is ready for lasting use.

### Product Details

Code:	LAM-SE-8-365
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	8mm
Width:	133mm
Length:	665mm
Coverage per pack:	1.238
AC rating:	AC4 - Heavy Domestic

### Warranty

Residential:	25 Years
Commercial:	N/A

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes Water Systems

### Technical

Water rating:	N/A
Technical Class:	32
Fire resistance:	EN 13501
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
 Tel: 02476 012840 | Fax: 02476 397828  
 info@ukflooringdirect.co.uk  
 ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.